



Room Air Conditioners: TwinTemp®



• EL36L35A Profile

- 36000/35700 BTU Cooling
- 17300/14300 BTU Heating
- 18.0/19.6 Cooling Amps
- 24.0/22.4 Heating Amps
- Moisture removal - 11 pints/hour
- Net weight - 220 lbs.
- 8.5/8.5 EER
- 230/208 Volts
- 4235/4200 Cooling Watts
- 5500/4650 Heating Watts
- Room Air Circulation 725 CFM
- Circuit Breaker Rating: 250V - 30A

TwinTemp® Models

- EM24L35
- EL36L35A
- EM18L34
- EQ08L11
- ES12L33
- ES16L33

TwinTemp® STANDARD FEATURES:

- Deluxe features with manual controls
- High efficiency with EERs up to 12.0 including 3 Energy Star models
- MoneySaver® setting saves energy by turning the fan on and off with the compressor (Not available on EQ08L11)
- Three cooling and 3 heating speeds, plus fan only setting (Two cooling, two heating on EQ08L11)
- Slide out chassis for easier installation and maintenance
- Washable, antimicrobial filter for protection against fungal and bacterial growth
- Fresh air intake and stale air exhaust
- Defrost control
- 8-way air flow control



Plug face:
NEMA # 6-30P

L Chassis Dimensions

Height	Width	Depth with Front	Depth (Hood to Louvers)	Minimum Extension into Room	Minimum Extension Outside	Window Width		Thru-the-Wall Finished Hole	
						Min.	Max.	Height	Width
20 3/16"	28"	33 5/8"	16 1/2"	3 1/16"	18 15/16"	29 7/8"	42"	20 3/8"	28 1/4"

Installation Notes

- Supply Cord - All with right angle plug 6' on 115V (7' on XStar models); 5' on all 230/208V.
- Room air conditioners include accessories for window or thru-the-wall installation.
- TWINTEMP® models include accessories for thru-the-wall installation only. Window mounting requires use of optional accessory kit as listed below:
 - **WIKQ:** EQ08L11, YQ07L10
 - **WIKS:** ES12L33, ES16L33, YS09L10, YS13L33
 - **WIKM:** EM18L34, EM24L35, YM18L34
 - **WIKL:** EL36L35, YL24L35