

PORTABLE AIR CONDITIONERS





ZoneAire. PORTABLE AIR CONDITIONERS

REMOTE	24-HOUR	BUCKETLESS	EZ-ROLL
CONTROL	TIMER	DESIGN	CASTERS
\checkmark	$\mathbf{\overline{\mathbf{N}}}$	\checkmark	$\mathbf{\overline{\mathbf{N}}}$

Features

- 40% FASTER COOLING with dual hose exhaust
- Remote control operation
- Self evaporative condensate system
- 24 hour timer
- 3 fan speeds
- Plugs into standard 115 volt outlet
- Cool/fan only/dehumidify
- Exhaust hoses and window kit included

Ideal for these applications

- Workshops and garages
- Home offices
- Dorm rooms
- Bedrooms, attics and basements
- Sunrooms/ enclosed patios
- Supplemental or emergency cooling anywhere



Specifications

Model		P09A	P12A
PERFORMANCE			
Cooling Capacity	BTU/h	8900	11500
Energy Efficiency Rating	EER	9.6	8.9
SPECIFICATIONS			
Rated Current	Amps	9.8	12.0
Refrigerant Type		R-	22
Power Supply	Volts	1.	15
	W	19 1/4	
Dimensions- Inches	Н	33 1/2	
	D	15 1/2	
Net Weight	Lbs.	80	86

Model Number	Circuit Rating	Plug Face	Wall Outlet
	Breaker or T-D Fuse	(NEMA#)	Appearance
P09A, P12A	125V - 15A	5 - 15P	

Portable Accessories


DUAL INTAKE/ EXHAUST HOSES (Included) Flexible, heavy duty intake/ exhaust hoses extend from 24" to 60". The hoses can be vented through a window or through a wall opening to the outside.



Venting of the unit to the outside is required for operating efficiency.

WINDOW SLIDER KIT (Included)





Fits HORIZONTAL or VERTICAL WINDOWS WINDOW OPENING: Minimum: 26"* Maximum: 46"

* Window slider kit can be trimmed to fit a smaller opening.





Friedrich Air Conditioning Co. | P.O. Box 1540 | San Antonio, TX 78295-1540 | (800) 541-6645 | fax (210) 357-4480 | www.friedrich.com PAC-08 Printed in USA

Self evaporative condensate system means no bucket to empty. If tank should become full, the unit will automatically shut off and unit can be

Bucketless design

drained through the water outlet drain.