SPECIFICATIONS-ELECTRIC RANGETOP

Description	VERT301-4B		DERT301-4B		DERT361-5B	
Overall Width	29 7/8" (75.9	cm)	29 7/8" (75.9 cm)		35 7/8" (91.1 cm)	
Overall Height	BASE HEIGHT		BASE HEIGHT			
	To top of		To top of			
	glass frame - 7 7/8" (20.0 cm)		side trim - 6 1/8" (15.6 cm)			
	ADDITIONS T	TO BASE HEIGHT				
To top of island trim	add 1 1/4" (3.2 cm)		add 0" (0 cm)			
To top of backguard	add 6" (15.2 cm)		add 6" (15.2 cm)			
To top of high-shelf	add 23 1/2" (59.7 cm)		add 23 1/2" (59.7 cm)			
Overall Depth from	To end of:					
Rear	side panel - 24" (61.0 cm)		24 7/16" (62.1 cm)			
	control panel	- 25 15/16" (65.9 cm)	26 1/8" (66.35 cm)			
	knobs -	27 7/16" (69.7 cm)	27 5/			
Cutout Width	30" (76.2 cm)		30" (76.2 cm)		36" (91.4 cm)	
Cutout Height	7 1/2" (19.1 cm)		5 3/4" (14.6 cm)		5 3/4" (14.6 cm)	
Cutout Depth	24" (61.0 cm)		24 7/16" (62.1 cm)		24 7/16" (62.1 cm)	
Electrical Connection	onnection 40 amp		40 amp		50 amp	
Requirements	3-Wire, 240/208 VAC, 60 Hz. Unit is equipped with No. 10 ground wire in conduit. Should be					Should be
	fused separately.					
Maximum Amps	240V- 34.6 amps 208V- 29.8 amps		240V- 35.0 amps		240V- 45.0 amps	
			208V- 30.3 amps		208V- 40.0 amps	
Surface Elements	<u>240V</u>	<u>208V</u>	<u>240V</u>	<u>208V</u>	<u>240V</u>	<u>208V</u>
Left Front	1500 watts	1125 watts	1800 watts	1350 watts	1800 watts	1350 watts
Bridge	N/A	N/A	800 watts	600 watts	800 watts	600 watts
Left Rear	2400 watts	1800 watts	1800 watts	1350 watts	1800 watts	1350 watts
Center	N/A	N/A	N/A	N/A	2700 watts	2025 watts
Right Front	1800 watts	1350 watts	1500 watts	1125 watts	1500 watts	1125 watts
Bridge	800 watts	600 watts	N/A	N/A	N/A	N/A
Right Rear	1800 watts	1350 watts	2500 watts	1875 watts	2200 watts	1650 watts
Approximate	110 lbs. (49.5 kg)		52 lbs. (23.4 kg)		63 lbs. (28.4 kg)	
Shipping Weight						

Minimum clearances from adjacent combustible construction

- •Cooking surfaces and below (36"[91.4 cm] and below)
 - •Sides- 0"
 - •Rear- 0" with backguard or highshelf; 0" with island trim and non-combustible wall;
 - 6" (15.2 cm) with island trim and combustible rear wall
 - •Top grate support 36" (91.4 cm)
- •Above cooking surface (above 36"[91.4 cm])
 - •Sides- 6" (15.2 cm)
 - •Within 6" (15.2 cm) side clearance, wall cabinets no deeper than 13" (33.0 cm) must be minimum 18" (45.7 cm) above cooking surface.
 - •Wall cabinets directly above product must be minimum 36" (91.4 cm) above cooking surface

It is not recommended to install two or more units side by side.