SPECIFICATIONS-ELECTRIC RANGETOP

Description	VCRT300			VIRT300			
Overall Width	29 7/8" (75.9 cm)						
Overall Height from	BASE HEIGHT ADDITIONS TO BASE HEIGHT						
Bottom	To top of glass frame		To top of island trim - add 1 1/4" (3.2 cm)				
	7 7/8" (20.0 cm)		To top of backguard - add 6" (15.2 cm)				
	To to			p of high-shelf - add 23 1/2" (59.7 cm)			
Overall Depth from	To edge of sid	de panel -	24" (61.0 cm)				
Rear	To end of cor	itrol panel -	25 15/16" (6	25 15/16" (65.9 cm)			
	To end of kno	bs -	27 7/16" (69	27 7/16" (69.7 cm)			
Cutout Width	30" (76.2 cm)						
Cutout Height	7 1/2" (19.1 cm)						
Cutout Depth	24" (61.0 cm)						
Electrical	3-Wire, 240/208 VAC, 60 Hz, electrical connection.						
Requirements	Unit is equipped with No. 10 ground wire in conduit. Should be fused separately.						
Maximum Amps	240v - 37.9 amps			240v - 40.0 amps			
	208v - 32.8 amps			208v - 34.6 amps			
Surface Element		<u>240V</u>	<u>208V</u>		<u>240V</u>	<u>208V</u>	
Rating	Left Front	2500 watts	1875 watts	Left Front	2700 watts	2025 watts	
	Left Rear	1500 watts	1125 watts	Left Rear	1800 watts	1350 watts	
	Right Front	1200 watts	900 watts	Right Front	1200 watts	900 watts	
	Right Rear	3300 watts	2475 watts	Right Rear	3300 watts	2475 watts	
Approximate	110 lbs. (49.5 kg)						
Shipping Weight							

Minimum clearances from adjacent combustible construction

- •Cooking surfaces and below (36"[91.4 cm] and below)
 - •Sides- 0"
 - •Rear- 0" with backguard or highshelf; 0" with island trim and non-combustible wall; 6" (15.2 cm) with island trim and combustible rear wall
 - •Top grate support 36" (91.4 cm)
- •Above cooking surface (above 36"[91.4 cm])
 - •Sides- 6" (15.2 cm)
 - •Within 6" (15.2 cm) side clearance, wall cabinets no deeper than 13" (33.0 cm) must be minimum 18" (45.7 cm) above cooking surface.
 - •Wall cabinets directly above product must be minimum 36" (91.4 cm) above cooking surface

PROXIMITY TO CABINET INSTALLATION

- 1. This rangetop may be installed directly adjacent to existing 36" (91.4 cm) high base cabinets.
- 2. The rangetop CANNOT be installed directly adjacent to sidewalls, tall cabinets, tall appliances, or other side vertical surfaces above 36" (91.4 cm) high. There must be a minimum of 6" (15.2 cm) side clearance from the rangetop to such combustible surfaces above the 36" (91.4 cm) counter height.
- 3. Within the 6" (15.2 cm) side clearance to combustible vertical surfaces above 36" (91.4 cm), the maximum wall cabinet depth must be 13" (33.0 cm) and wall cabinets within this 6" (15.2 cm) side clearance must be 18" (45.7 cm) above the 36" (91.4 cm) high countertop.
- 4. Wall cabinets above the rangetop must be a minimum of 36" (91.4 cm) above the rangetop cooking surface for the full width of the rangetop.



