COMBINATION INSTALLATIONS

Document # PGCI-009

RGC/SGM Series Drop-In Gas Cooktop, PLANNING **RV Series Raised Vent, Single Wall Oven** GUIDE ife of the Kitchen Wall board WARNING Wall \Diamond Observe all governing codes and ordinances during Backsplash planning and installation. Contact your local building department for further information. 5/8" (16 mm) Min. \Diamond All appliances must be installed in accordance with the countertop overhang accompanying installation instructions. Back of cabinet interior All tolerances: +1/16", -0, (+1.6 mm, -0) unless otherwise stated Cooktop (102 mm) Stiffner Oven Raised vent 5/8" (16 mm) Min. gap behind raised vent to allow for stiffner 22 1/4" (565 mm) Cooktop and vent cutout 6 1/2" Cabinet face (165 mm) Stiffner Dacor RGC/SGM drop-in cooktop 1/4" (6 mm) gap RV30/36/46 with minimum remote or in-line blower 5/8" (16 mm) Min. gap 30 3/4" (781 mm) behind raised vent to Minimum from allow for stiffner finished countertop to Dacor Discovery or oven platform Renaissance single wall oven 36" (914mm) Typical 1/8" (3 mm) Min. gap counter height between raised vent and wall oven Bottom exhaust configuration shown Support platform 3/4" (19 mm) Min. Thickness 1 1/2" (38 mm) Adjustable support leg Min. oven platform height Finished floor 29 3/8" (746 mm) Min. Cabinet face

Cutaway Side View

www.Dacor.com Phone: (800) 793-0093 Specifications are subject to change without notice. See installation instructions for additional details.

CI.1

Revised 05/08/09 Page 1/1