



# Uni-Fit Thru-the-wall

Cooling only and electric heat

PURCHASER		P.O. #	DATE
PROJECT		LOCATION	
ENGINEER		ARCHITECT	
SUBMITTED BY		FOR APPROVAL	FOR REFERENCE

ITEM	PLAN DESIGNATION	QUANTITY	COOLING BTU/H	VOLTAGE	FRIEDRICH MODEL

## Universal Fit for Easy Replacement

### Chassis installs into existing 26" sleeves

REMOTE CONTROL	12-HOUR TIMER	MONEY SAVER FEATURE
✓	✓	✓

#### COOLING ONLY & ELECTRIC HEAT

- Rotary compressors provide quiet, dependable performance
- Six-way air flow control
- Stale air exhaust
- Auto re-start
- Washable/reusable filter
- Seacoast protection



HEAT/COOL MODELS feature mechanical controls, two cooling speeds, two heating speeds, plus one fan-only setting.

COOLING MODELS feature electronic controls with remote control, Money Saver® setting that saves energy by cycling the fan with the compressor and three cooling/three fan-only speeds.

#### Digital Controls Feature (cool only models)

- 12 hour programmable timer
- Money Saver® setting saves energy by cycling the fan with the compressor

Sleeve Dimensions	Friedrich USC Sleeve	Amana	Carrier (51S Series)	Fedders/Emerson/Friedrich WSC	Emerson/Fedders	GE/Hot-point	Whirlpool	White-Westinghouse/Frigidaire/Carrier (52F Series)
Height (inches)	15 17/32	15 5/8	16 7/8	16 3/4	15 3/4	15 5/8	16 1/2	15 1/4
Width (inches)	25 7/8	26	25 3/4	27	26 3/4	26	25 7/8	25 1/2
Depth (inches)	16 23/32	16 7/8	18 5/8	16 3/4 or 19 3/4	15	16 7/8	17 1/8 or 23	16, 17 1/2 or 22

Units are shown without USC sleeve (USC sleeves sold and shipped separately)




5 ENERGYSTAR® models



# Specifications ★ ENERGY STAR® models

Model	Cooling Capacity BTU/h	Heating Capacity BTU/h	Volts Rated	Cooling Amps	Cooling Watts	Heating Amps	Heating Watts	Energy Efficiency Ratio EER	Moisture Removal Pints/Hr.	Room Side Air Circulation	Weight Lbs. Ship/Net
UNI-FIT											
★ US08B10A	8000	—	115	7.5	830	—	—	9.6	2.2	260	77/73
★ US10B10B	9800	—	115	9.6	1040	—	—	9.4	3.2	270	82/78
★ US10B30A	10000/9800	—	230/208	4.7/5.2	1060/1040	—	—	9.4	3.2	285	82/78
★ US12B10B	11500	—	115	11.2	1220	—	—	9.4	3.8	290	84/80
★ US12B30C	11500/11200	—	230/208	5.6/6.0	1250/1190	—	—	9.4	3.8	290	84/80
US14B30A	13000/12600	—	230/208	7.0/7.5	1530/1480	—	—	8.5	4.0	300	88/84
UE08A13B	8000	3850	115	7.5	830	10.7	1230	9.6	2.2	260	77/73
UE10A33B	10000/9800	11200/9200	230/208	4.7/5.2	1060/1040	15.3/14.0	3500/2900	9.4	3.2	285	82/78
UE12A33C	11500/11200	11200/9200	230/208	5.6/6.0	1220/1190	15.3/14.0	3500/2900	9.4	3.8	290	84/80

## Plug Face/ Circuit Rating

WallMaster Model Number	Uni-Fit Model Number	Circuit Rating Breaker or T-D Fuse	Plug Face (NEMA#)	Power Cord Length (ft.)	Wall Outlet Appearance
WS08B10A, WS10B10A, WS14B10A	US08B10A, UE08A13B US10B10B, US12B10B	125V - 15A	5 - 15P	6	
WS10B30A, WS13B30B, WS16B30A	US10B30A, US12B30C, US14B30A	250V - 15A	6 - 15P	4	
WE10B33C, WE13B33C, WE16B33C, WY10B33C, WY13B33C	UE10A33B, UE12A33C	250V - 20A	6 - 20P	4	

Power cords are located on front left of WallMaster models and on front right of Uni-Fit models.



As an ENERGY STAR® partner, Friedrich Air Conditioning Co. has determined that the selected ENERGY STAR® models (★) meet the ENERGY STAR® guidelines for energy efficiency.

