

Uni-Fit Thru-the-wall

Cooling only and electric heat

PURCHASER	P.O. #	DATE
PROJECT	LOCATION	
ENGINEER	ARCHITECT	
SUBMITTED BY	FOR APPROVAL	FOR REFERENCE

ITEM	PLAN DESIGNATION	QUANTITY	COOLING BTU/H	VOLTAGE	FRIEDRICH MODEL

REMOTE	12-HOUR	MONEY SAVER
CONTROL	TIMER	FEATURE
lacktriangledown	\bigcirc	

Universal Fit for Easy Replacement Chassis installs into existing 26" sleeves

COOLING ONLY & ELECTRIC HEAT

- Rotary compressors provide quiet, dependable performance
- · Six-way air flow control
- Stale air exhaust

- Auto re-start
- · Washable/reusable filter
- · Seacoast protection
- HEAT/COOL MODELS feature mechanical controls, two cooling speeds, two heating speeds, plus one fan-only setting.

COOLING MODELS feature electronic controls with remote control, Money Saver® setting that saves energy by cycling the fan with the compressor and three cooling/three fan-only speeds.

REMOTE CONTROL FEATURES (cool only models)

- 12 hour programmable timer
- Money Saver® setting saves energy by cycling the fan with the compressor

Sleeve Dimensions	Friedrich USC Sleeve	GE	Amana	Whirlpool/ Fedders	Frigidaire
Height (inches)	15 17/32	15 5/8	15 5/8	15 3/4	15 7/16
Width (inches)	25 7/8	26	26	26 3/4	25 7/8
Depth (inches)	16 23/32	16 7/8	16 7/8	15	18





Units are shown without USC sleeve (USC sleeves sold and shipped separately)

Specifications



Model	Cooling Capacity BTU/h	Heating Capacity BTU/h	Volts Rated	Cooling Amps	Cooling Watts	Heating Amps	Heating Watts	Energy Efficiency Ratio EER	Moisture Removal Pints/Hr.	Room Side Air Circulation	Net Weight Lbs.
UNI-FIT											
★ US08B10A	8000	_	115	7.5	830	_	_	9.6	2.2	260	73
US10B10A	9800	_	115	10.2	1110	_	_	8.8	3.2	285	78
★ US10B30A	10000/9800	_	230/208	4.7/5.2	1060/1040	_	_	9.4	3.2	285	78
US12B10A	11500	_	115	12.0	1310	_	_	8.8	3.8	290	80
US12B30B	11500/11200	_	230/208	6.0/6.4	1310/1270	_		8.8	3.8	290	80
US14B30A	13000/12600	_	230/208	7.0/7.5	1530/1480	_	_	8.5	4.0	300	84
UE08A13B	8000	3850	115	7.5	830	10.7	1230	9.6	2.2	260	73
UE10A33B	10000/9800	11200/9200	230/208	4.7/5.2	1060/1040	15.3/14.0	3500/2900	9.4	3.2	285	78
UE12A33B	11500/11200	11200/9200	230/208	6.0/6.4	1310/1270	15.3/14.0	3500/2900	8.8	3.8	290	80

Plug Face/ Circuit Rating

Uni-Fit Model Number	Circuit Rating Breaker or T-D Fuse	Plug Face (NEMA#)	Wall Outlet Appearance
US08B10A, UE08A13B US10B10A, US12B10A	125V - 15A	5 - 15P	1.
US10B30A, US12B30B, US14B30A	250V - 15A	6 - 15P	•
UE10A33B, UE12A33B	250V - 20A	6 - 20P	••



As an Energy Star® partner, Friedrich Air Conditioning Co. has determined that the selected Energy Star® models (\bigstar) meet the Energy Star® guidelines for energy efficiency.







