INDUCTION COOKTOP



LCE30845

30" Induction Cooktop

Cooking Performance

- 4 Cooking Elements with Bridge
- 100% Induction Bridge Element

Style and DesignPremium Stainless Steel Trim

Convenience Features

- SmoothTouch[™] Controls
- Premium Grade Griddle Included





INDUCTION COOKTOP

How Does Induction Work?

The electromagnetic energy generated by an induction coil reacts only with iron-like metals, not with ceramic surfaces. The pot absorbs the electromagnetic energy, and converts it into heat. Only the bottom of the pot is heated, which guarantees even heating, safety and energy savings.

Bridge Element with 100% Induction Cooking

In addition to being used separately, the left front and left rear elements can be joined by the bridge element to evenly heat longer pans and griddles; perfect for your pancakes and French toast. Unlike most manufacturers, LG's induction cooktop features a bridge element that uses 100% induction, with no need for a traditional heating element.

SmoothTouch[™] Controls

Activate and control the temperature setting with the touch of a finger.



Cooking Zone Layout

Accommodates all kinds of cooking needs from large pan to the supplied griddle.

Streamlined Design

Elegant ceramic glass with a premium stainless steel trim will complement any kitchen décor.

_	LCE30845
Туре	Electric Induction
Size	30″
CONFIGURATION	
No. of Cooking Zones	4 (Plus Bridge)
Cooking Zone Configuration (Normal/Boost)	1 10// 1 1 1 1 1 2 1001/ /7 7 001/0
Large: Right Rear Small: Right Front	1 – 10" Induction (2400W/3300W) 1 – 6" Induction (1400W/1800W)
Standard: Left Side	2 - 7" Induction (1800W/2400W)
Bridge: Left Side	1 – 7" x 16 5/8" Induction
Power Boost* Warming Function	All Cooking Zones (Minus Bridge) All Cooking Zones
CONTROLS	0
Туре	Electronic Glass Touch
Location	Front
Touch Pads	18
Kitchen Timer	1 – 99 min.
SAFETY FEATURES	
Automatic Shut-Off	17 Hours
Child Lock	•
Hot Surface Indication	•
COLOUR	-
Surface / Trim	Black / Stainless Steel
MATERIALS/FINISHES	Slack / Stalliess Steel
Control Panel	Ceramic Glass
Cooking Surface	Ceramic Glass
Frame (Trim)	Stainless Steel
POWER SOURCE	Stalliess Steel
	240V/208V, 60Hz AC
Electric Supply	
Max. Amp Load	32 Amp
Power Cable Location	Left Rear
Total Connected Load	7.4kW @ 240V / 6.7kW @ 208V
Power Source	Electric
DIMENSIONS	
Width	30 3/16" (78.3cm)
Height	2 3/16" (5.5cm)
Depth	21 1/2" (54.5cm)
Product Weight	40.1 lbs (18.2 Kg)
Shipping Weight	52.3 lbs (23.7 Kg)
CUTOUTS	
Width (Opening)	29 3/8" Min (74.6cm)
Depth (Opening)	20 1/4" Min (51.4cm)
ACCESSORIES	
Griddle Pan	٠
UPC CODE	
LCE30845	048231 316033
WARRANTY	
	1 Year Parts and Labour
	5 Years Parts on Cooktop and Induction C

Design and specifications are subject to change without notice. All trademarks are property of their respective owners.

*Power Boost is available on one cooking zone per side at a time.



LG ELECTRONICS CANADA INC. 550 Matheson Blvd. East, Mississauga, ON L4Z 4G3 Tel: 905.568.6800 | Fax: 905.507.9649 | LG.ca Customer Parts & Service 1-888-LG-CANADA | Igservice.com