

WALL-MOUNT CHIMNEY HOOD

The clean lines, beautifully sloping angles and stainless steel finish of Varna make a striking visual statement...a "pro kitchen" look that complements contemporary kitchen décor. Available in 30" or 36" width, Varna features include a powerful 600 CFM blower, halogen lighting with 2 light intensities, dishwasher-safe aluminum mesh filters and high-tech multi-function LCD controls that deliver convenience and safety. Designed for standard ducted installation, Varna can also be installed as a recirculating system using the Recirculating Kit, available as an accessory.

FEATURES

· Advanced Electronic Touch Controls

State-of-the-art electronics deliver maximum user convenience and control. LCD function display with elegant blue illumination combined with low-profile, easy-to-clean touchpads is your interface with a multi-function control system, including...



- · On/Off control
- · Programmable timer and buzzer
- · Four blower speeds
- · Clock

- HeatGuard[™] automatically adjusts blower speed if heat exceeds 158°F for safety and convenience
- · Two light intensities
- Filter Saturation Monitor detects excessive levels within both grease and charcoal filters
- · 600 CFM 4-Speed Internal Blower
- 2 Halogen Lamps with two light intensities (120V 50W bulbs included)
- Dishwasher-Safe Anodized Aluminum Mesh Filters (2 with 30" unit, 3 with 36" unit)






Elica-Patented Stainless Steel Micro Hole Filter

Available as an optional upgrade (see back for accessory details)

- Telescopic Chimney Extension For ceiling heights 7' 5" to 9' 2"
- · 8" Round Duct Transition
- One-Way No Return Valve eliminates outside air drafts.



MODEL			DIMENSION	S	SHIPPING
NUMBER	FINISH	WIDTH	DEPTH	HEIGHT	WEIGHT
EVR630SS	Stainless Steel	30"	19-11/16"	10-1/4"	55 lbs.
EVR636SS	Stainless Steel	36"	19-11/16"	10-1/4"	60 lbs.

HOOD MOUNTING HEIGHT ABOVE COOKING SURFACE

G	AS	ELEC	TRIC
minimum	maximum	minimum	maximum
30"	34"	24"	30"

CHIMNEY HEIGHT (based on recommended mounting heights listed above)

DUC	CTED	RECIRC	CULATING
Gas min./max.	Electric min./max.	Gas min./max.	Electric min./max.
7' 11" - 9' 2"	7' 5" - 8' 10"	7' 11" - 9' 6"	7' 5" - 9' 2"

BLOWER PERFORMANCE

SPEED LEVEL	AIRFLOW IN CFM (CUBIC FEET PER MINUTE)	SOUND LEVEL (IN SONES)
1	160	1.7
2	280	3.3
3	475	6.0
4	600	8.2

VARNA ACCESSORIES

MODEL NUMBER	DESCRIPTION	SHIPPING WEIGHT
EXXRCK06	Recirculating Kit	6.6 lbs
EXXGFKMH	Stainless Steel Micro Hole Filter	5.5 lbs
EXXGFKBS	Stainless Steel Baffle Slot Filter	6.6 lbs





ELECTRICAL:

AC Input: 120V - 60Hz, AC Power Max.: 550W at 4.6 Amps