

## AMANA 26" BUILT-IN AIR CONDITIONERS

Through-the-wall design for flush-mount applications

Cooling Only or Electric Heat or Heat Pump Models

# Complete guest comfort with easy to use controls

### Specifications for:

#### Cooling Models:

PBC092A00MA  
PBC122A00MA  
PBC093A00MA  
PBC123A00MA

#### Electric Heat Models:

PBE093A35MA  
PBE123A35MA

#### Heat Pump Models:

PBH092A12MA  
PBH093A35MA  
PBH113A35MA



PBC - Cooling only controls not shown.



- **High Energy Efficiency with models up to 9.5 EER** saving you money when compared to other competition models.
- **Easy removable condenser top** that allows for quick and complete cleaning of outdoor coils. This access for cleaning the outdoor coil enables easy removal of dirt and debris to dramatically lengthen the life of the compressor and other sealed system components. Six easy access screws and let the cleaning begin! Not available on competitor models!
- **Easy access slide out filter** has a permanent polypropylene filter mesh that is easy to remove and clean.
- **Accessory Wall Sleeve: PBWS01A** is a solid-side, heavily insulated metal sleeve. It includes a stamped aluminum exterior grille with a weather-seal rear enclosure for installation without the chassis. The sleeve has a solid bottom for complete weather-tight installation. An optional PBWMFC can be used when a more permanent weather seal is needed for sleeves installed without the chassis.
- **100% Full Factory run test** on all units for high reliability and dependability. Units start the first time – every time!
- **4-Way Adjustable airflow** to allow for cooling or heating to any part of the room.
- **Quiet Operation.** Designed with guest comfort in mind — providing reliable, quiet operation for years to come.

Heating & Air Conditioning  
**Amana**<sup>®</sup>

It's just what you'd expect  
from an industry leader.

**Cooling Only Models**

**Electric Heat Models**

**Heat Pump Models**

Goodman Model	PBC092A00MA	PBC122A00MA	PBC093A00MA	PBC123A00MA	PBE093A35MA	PBE123A35MA	PBH092A12MA	PBH093A35MA	PBH113A35MA
<b>General Features:</b>									
Voltage	115	115	230 / 208	230 / 208	230 / 208	230 / 208	115	230 / 208	230 / 208
Approx. chassis weight	80 lbs	80 lbs	80 lbs	80 lbs	85 lbs	85 lbs	85 lbs	85 lbs	85 lbs
Approx. shipping weight	95 lbs	95 lbs	95 lbs	95 lbs	98 lbs	98 lbs	98 lbs	98 lbs	98 lbs
<b>Cooling:</b>									
Capacity / BTUH	9,300	11,600	9,300 / 9,100	11,600 / 11,200	9,300 / 9,100	11,600 / 11,200	9,000	9,000 / 8,700	11,000 / 10,700
Amps	8.8	10.7	4.2 / 4.6	5.3 / 5.8	4.2 / 4.5	5.4 / 5.8	8.5	4.2 / 4.6	5.4 / 5.7
Watts	1,010	1,227	962 / 947	1,228 / 1,208	964 / 931	1,231 / 1,213	985	967 / 953	1,228 / 1,195
CFM	258	270	258	270	258	270	258	258	270
E.E.R.	9.5	9.4	9.5 / 9.5	9.4 / 9.4	9.5 / 9.5	9.4 / 9.4	9.4	9.5 / 9.5	9.0 / 9.0
Energy Star Qualified	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	No
Dehumidification - pts/hr	2.5	3.4	2.5	3.4	2.5	3.4	2.5	2.5	3.4
<b>Electric Heat:</b>									
Capacity / BTUH	n/a	n/a	n/a	n/a	11,000 / 9,000	11,000 / 9,000	3,900	11,000 / 9,000	11,000 / 9,000
Amps	n/a	n/a	n/a	n/a	15.2 / 13.8	15.2 / 13.8	12.0	15.2 / 13.8	15.2 / 13.8
Watts	n/a	n/a	n/a	n/a	3,500 / 2,877	3,500 / 2,877	1,150	3,500 / 2,877	3,500 / 2,877
<b>Heat Pump: (Reverse cycle)</b>									
Capacity / BTUH	n/a	n/a	n/a	n/a	n/a	n/a	8700	8,500 / 8,200	10,100 / 9,800
Amps	n/a	n/a	n/a	n/a	n/a	n/a	7.5	3.7 / 4.0	4.6 / 4.8
Watts	n/a	n/a	n/a	n/a	n/a	n/a	870	857 / 832	1,055 / 1,012
C.O.P	n/a	n/a	n/a	n/a	n/a	n/a	3.0	3.0 / 3.0	2.7 / 2.7
Adjustable changeover thermostat	n/a	n/a	n/a	n/a	n/a	n/a	Yes	Yes	Yes
Thermostatic drain valve	n/a	n/a	n/a	n/a	Yes	Yes	Yes	Yes	Yes
<b>Electrical Data:</b>									
Circuit Breaker Size	15-amps	15-amps	15-amps	15-amps	20-amps	20-amps	15-amps	20-amps	20-amps
Plug type	Parallel	Parallel	Tandem	Tandem	Perpendicular	Perpendicular	Parallel	Perpendicular	Perpendicular
Power cord length	8.0' w/LCDI	8.0' w/LCDI	6.0' w/LCDI	6.0' w/LCDI	6.0' w/LCDI	6.0' w/LCDI	8.0' w/LCDI	6.0' w/LCDI	6.0' w/LCDI

**Note:** Units ship without the optional PBWS01A wall sleeve and require a solid-side sleeve for field installation. If installing into existing sleeves, call your Amana sales person for compatibility assessment or adapter kits. The product warranty can be voided if units are installed into improper sleeves or used with improper grilles.

**Features:** (all models)

Agency Approval	U.L. (Under Writers Laboratory) listed; USA and Canada
Chassis Type	Slide-out for easy installation and service accessibility
Fan speeds:	2 speeds: High & Low
Energy Saver	Yes - ( Cooling only - Auto fan operation )
Fan ONLY	Yes - High Speed
Exhaust CFM	300
Discharge air	Top discharge with 4-way adjustable air throw
Slide-out-filter	Top Pull-out Polypropylene - Permanent filter that is washable
Condensate drain spout	Yes - external drain spout on the PBWS01A optional wall sleeve

Dimensions:	Height	Width	Depth
PBWS01A Sleeve	15 5/8"	26.0"	16 7/8"
With chassis installed	Depth with chassis installed and room front cover attached = 21 7/8"		
Sleeve Cut-outs:	15 13/16"	26 3/16"	Maximum wall thickness = 16 3/8"

**Plug Type:**

Parallel      Tandem      Perpendicular



15 Amps      15 Amps      20 Amps  
125 Volts      250 Volts      250 Volts



**Optional Accessories:**

PBWS01A	Insulated metal sleeve for installation of 26" Built-In Air Conditioners; solid side and solid bottom with weather board and stamped aluminum grille. Color: Beige
PBAGK01TB	Architectural grille kit for use with PBWS01A sleeve and 26" Built-In Air conditioners in beige.
PBAGK01SB	Architectural grille kit for use with PBWS01A sleeve and 26" Built-In Air conditioners in custom colors
PBWMFC01A	An insulated metal cover for use when PBWS01A is installed without 26" Built-In Air Conditioner
PBFAK01A	Sleeve adapter kit; converts Fedders BSAOOC & Friedrich WSC 27" wall sleeves for use with Amana 26" Built-In Air Conditioners

**5-Year Parts and Labor Warranty:**

1-Year entire unit and 5-Year sealed system components. Goodman will repair or replace any factory defective part or sealed system leak caused by a defective part and pay labor and associated service costs directly related to the part replacement or repair. See product warranty for complete details.

Call your Amana sales representative at

**800-647-2982**

for complete details.



It's just what you'd expect from an industry leader.