

Viking Outdoor Ultra-Premium 100 and 300 Series Gas Grills



Common Features – 100 and 300 Series

- 30" and 36" widths
- New 24.5" cutout depth
- Polished/brushed edge canopy design along with Classic Viking cosmetic features
 - Cast metal, black knobs
 - Refined landing ledge design
 - Refined handle and endcaps
- 304 Stainless Steel burners – 25K BTU
- Ceramic heat distribution system
- White briquettes with "flip-clean" self-clean design
- Provides even heat distribution
- Discourages flare-ups
- Hermetically sealed numerical thermometer that will not fog
- Insulated jacket accessory required for combustible installations

300 Series Dedicated Features

- Push and turn 120V electric ignition system provides a positive, consistent, and continuous spark for easy ignition
- Exclusive – Automatic reignition system
- Halogen lighting
- Stainless Steel cooking grates
- Rotisserie System
 - Gourmet-Glo™ 15,000 BTU one-piece infrared rotisserie burner
 - Fully enclosed SS rod with stainless forks
 - Heavy-duty rotisserie motor

100 Series Dedicated Features

- 9V battery ignition system
- Porcelain-coated steel grilling grates

Solid Viking Construction

- New "counter-depth" cutout

Easy Maintenance and Cleanup

- Full-width, pull-out drip tray

Optional Accessories

- Stainless steel carts (30" and 36" wide)
- Insulated Jackets – INJK30/INJK36

Exclusive Finish Details

- Available in Stainless Steel (SS)

Models

- VGBQ13002
- VGBQ13603
- VGBQ33002RE
- VGBQ33603RE

Warranty Highlights

- One year full covers all in-home repairs
- Five year limited – grill burner assemblies and porcelain grill grates
- Lifetime limited – porcelain grill grates and rust through on all stainless steel components including stainless steel grill burners

Basic Specifications

Description	OUTDOOR GAS 30" AND 36" WIDE 100 AND 300 SERIES GRILLS	
	VGBQ13002/VGBQ33002RE	VGBQ13603/VGBQ33603RE
Cutout Width	29 1/4" (74.2 cm)	35 1/4" (89.5 cm)
Cutout Depth	24 3/8" (67.9 cm)	
Cutout Height	10 1/8" (25.7 cm)	
Overall Width	30" (76.2 cm)	35 7/8" (91.1 cm)
Overall Depth	29" (73.6 cm)	
Gas Requirements	Natural: standard residential 1/2" (1.3 cm) ID gas service line. LP/Propane: Equipped with high-capacity hose/regulator assembly for connection to standard 5 gal., 20 lb. LP/Propane gas cylinder with a Type 1, QCC-1 connector or standard residential 1/2" (1.3 cm) ID gas service line	
Electrical Requirements	100 Series – 9-volt DC battery for electronic ignition 300 Series – 120VAC/60Hz; 3' (91.4 cm) power cord supply cord with 3-prong grounded plug attached to grill; 2' (61.0 cm) power cord supply with 3-prong grounded plug attached to rotisserie models	
Maximum Amp Usage	2.1 amps	2.2 amps
Grill Burner Rating	25,000 BTU NAT./22,500 BTU LP (7.3 kW NAT./6.5 kW LP)	
Rotisserie Burner Rating (300 Series)	15,000 BTU NAT./13,500 BTU LP (4.4 kW NAT./4.0 kW LP)	
Approximate Shipping Weight	325 lbs. (147.5 kg)	340 lbs. (154.0 kg)

Please do not prepare installation from brochure data only. See installation instructions for important clearance/installation information.

For product information, call 1-888-VIKING1 (845-4641), or visit the Viking Web site at vikingrange.com



All models with standard equipment are design-certified for residential installation.



Viking Range Corporation
111 Front Street, Greenwood, Mississippi 38930 USA
(662) 455-1200

© 2012, Viking Range Corporation.

To receive the most current specification sheets, visit Dimension Express at www.dexpress.com or call from your fax machine at (925)284-3558. Enter code #8051 for Viking Products. This will send you information on how to use the system and the corresponding model code numbers. Dimension Express customer support can be reached by email at: support@dexpress.com.