



CV-P12LX
CV-P10MX

Sharp's Portable Series Air Conditioners are easy to move from room to room. Both models provide quiet cooling with sleek and attractive styling and a Plasmacluster® ion generator. They can also be used as a dehumidifier to remove up to 65 pints of moisture from the air in a single day. A fully featured remote control with LCD display allows you to control each unit from anywhere in the room. The flexible exhaust hose and window adapter kit allow venting of the hot air, while keeping out rain and insects.

Features:

Portability – 4 Easy Roll Casters allow the air conditioner to be moved easily from room to room. The flexible exhaust hose and window adapter kit allow easy venting to the outside.

Full Function Remote Control with LCD Display – Control every function of the unit from virtually anywhere in the room. Change the mode of operation, adjust the fan speeds or activate the timer. The LCD display shows all of the current settings.

Plasmacluster® Ion Technology – Activate the Plasmacluster Ion generator to release positive and negative ions into the air.

Large Capacity Dehumidification – Use the dehumidify function to remove up to 65 pints of moisture from the air every 24 hours (The CV-P12LX removes up to 65 pints/24 hours).

Automatic Oscillating Louvers allow you to sweep the air throughout the room for better distribution and comfort.

4-Way Air Direction lets you direct the cool air where you need it most.

Bucketless Design – No water tank to empty. The built-in condensate disposal system sends the water out of the exhaust hose.

Library Quiet® – As low as 38 dB at Low Cool.

Complies with power cord regulations: Leakage Current Detection and Interruption Device (LCDI) included.



Specifications

| Models | CV-P10MX | CV-P12LX |
|--|---|---------------------------------------|
| BTU | 9,500 BTU/hr. at ASHRAE 128 Standard | 11,500 BTU/hr. at ASHRAE 128 Standard |
| Plasmacluster® Technology | Yes | |
| Controls | Cool, Dehumidify, Fan and Ventilate modes. Select the fan speed, adjust the temperature, activate the oscillating louvers or set the 12 hour on/off timer. | |
| Remote | Full Featured with LCD display. Allows complete control of the air conditioner from virtually anywhere in the room. | |
| Fan Speeds | 3 cooling speeds plus Mega Cool for maximum cooling performance. Auto Cool selects the best fan speed for your room conditions. 3 fan only speeds when cooling is not required. | |
| Window Kit Dimensions (in inches) | Approximate Height - Minimum 6 Approximate Width - Minimum 24 - Maximum 48 Can also be used in Sliding Windows | |
| 12 Hour Timer | Yes | |
| Permanent, Reusable Slide-out Filter | Yes | |
| Library Quiet® | Yes | |
| Air Direction | 4-Way | |
| CFM | 280 / 240 / 190 / 140 | 300 / 270 / 210 / 170 |
| Moisture Removal (pint/hr.) | 2.5 (60 pints/24 hours) | 2.7 (65 pints/24 hours) |
| Duct Length (in inches) | 59 | |
| Exhaust | Yes | |
| Unit Dimensions (w x h x d) (in inches) | 18.5 x 32.3 x 15.1 | |
| Net Weight (in pounds) | 84 | 86 |
| UPC | 074000662278 | 074000662063 |

Sharp, Library Quiet, Plasmacluster and all related trademarks are trademarks or registered trademarks of Sharp Corporation and/or its affiliated companies. All other trademarks are property of their respective owners.

Product specifications and design are subject to change without notice.

07L035



SHARP ELECTRONICS CORPORATION
 Sharp Plaza, Mahwah, NJ 07430-1163
 For more information call: 1-800-BE-SHARP
 www.sharpsusa.com