

# 301 SERIES DISHWASHER

## RDDB301 – 24" WIDE



### Multi-Level Power Wash

- Multi-level washing with two stainless steel wash arms
  - Largest and most powerful in industry
  - **Exclusive** – Flexible-Fluid™ coupling is blockproof and provides a direct water feed
- DishGuard™ protector prevents blockage from lower rack load and protects dishes
- Sliding detergent/rinse agent dispenser

### Five-Stage Filtration and Waste Removal System – Exclusive

- Prevents redeposit of food particles to deliver spot-free dishes
- Removable coarse strainer
- Triple-Clean™ filtration
  - Horizontal stainless steel fine mesh filter with 18 full-force, self-cleaning jets
  - Vertical stainless steel ultra-fine mesh filter
  - Small filter in sump assures 100% filtered water to wash arms
- Ultra-hard food waste disposer

### Sure-Temp™ Water Heating

- Automatically heats water to appropriate/selected temperature, assuring excellent washing results
- 1,200-watt HydroFlo™ water heater

### Condensate Quick Dry

- Moisture condensates on the cooler stainless steel tank door and drains to the sump area
- Quick and efficient drying

### Quiet Clean™ Performance Package

- Engineered top to bottom for the quietest operation possible
- Separate motor/pump assemblies for washing and draining
- Sound absorbing/heat retaining insulation

### “Load-As-You-Like” Sturdi-Bilt™ Racks

- Heavy-duty racks accommodate 15 international place settings of china in a single load
- Fully usable and extendable nylon-coated racks
- One-piece silverware/cutlery basket with lids
- Lower rack
  - Four rows of one-piece, three-position, fold-down tines
- Roller Bearing™ upper rack
  - **Exclusive** – Three rows of multi-position Hold-Tight™ dividers
  - One-piece stemware cradle/cup shelf

### Additional Construction and Safety Features

- **Exclusive** – Diamond-Brite™ stainless steel tank and inner door – brightly polished to protect long-term appearance
- Largest dishwasher tank/door
- Rigid steel braces
- Completely enclosed rustproof steel base/pan with removable front
- Fill and drain system
  - Fill valve
  - Backflow prevention valve
  - Overflow protector in base pan
- Door triple safety system – mechanical latch, electrical safety switch, and start button

### Cycles/Options

- Cycles – Pots/Pans, Normal Wash, Light/China, Rinse/Hold
- Options – Hi Temp Wash, Sanitized 155 Degrees F Rinse, Delay Start up to 4 hours
- Energy Star Qualified
- CEE Tier I Super Efficient
- NSF Certified

### Finishes

- Available in Stainless Steel (SS), Black (BK), and White (WH)



24" Wide Dishwasher

## Customizable Options

- Shipped standard with chrome handle inserts
- Create your own look with customizable handle inserts
- Accessory kits available in the following finishes:
  - Paintable clear plastic
  - Wood – cherry, oak, maple, and unfinished maple (can be stained to match existing cabinetry)

## Warranty Highlights

- Three-year full – complete dishwasher
- Ninety-day full – cosmetic parts such as glass, painted items, and decorative items
- Lifetime limited – tank and inner door
- Five-year limited – electronic controls, racks, motor/pump assemblies, and water distribution system



DESCRIPTION	24" WIDE DISHWASHER RDDB301
<b>Overall Width</b>	23 7/8" (60.6 cm)
<b>Overall Height from Floor</b>	33 7/8" (86.0 cm) minimum to 35" (89.0 cm) maximum
<b>Overall Depth from Rear with Door Panel Installed</b>	23 5/8" (60.0 cm) With door open – 49" (124.5 cm)
<b>Cutout Width</b>	24" (61.0 cm)
<b>Cutout Height</b>	34" (86.4 cm) minimum to 35" (89.0 cm) maximum
<b>Cutout Depth</b>	24" (61.0 cm)
<b>Electrical Requirements</b>	15.0 amps, 120V/60Hz, 3'9" (1.1m) electrical cord with 90-degree, 3-prong plug supplied with unit
<b>Water Heating Element Rating</b>	1,200 watts
<b>Inlet Water Temperature</b>	120° F (49° C) recommended; 5' braided stainless steel hose with 3/8" OD compression fitting supplied with unit
<b>Drain Hose</b>	7' (2.1 m), 1/2" (1.3 cm) ID "crimp-proof" flexible drain hose with clamp attached to dishwasher; connections provided for 5/8" (1.6 cm), 3/4" (1.9 cm), or 1" (2.5 cm), cut as required
<b>Drain Hose High Loop Required</b>	Height from floor – 20" (51.0 cm) minimum
<b>Approximate Shipping Weight</b>	147 lb. (66.2 kg)

Note: Please do not prepare installation from brochure data only. See installation instructions for important clearance/installation information.



Viking Range Corporation • 111 Front Street • Greenwood, Mississippi 38930 USA • (662) 455-1200  
For product information, call 1-888-VIKING1 (845-4641), or visit the Viking website at vikingrange.com.



© 2012, Viking Range Corporation • Specifications subject to change without notice.

