SunBriteTV_®

True Outdoor Televisions

MODEL 5565HD

| DISPLAY | |
|----------------------------------------------|------------------------------------------------------------------------------------------------------------------------------|
| AVAILABLE COLORS White Silver Black | <image/> <image/> |
| KEY FEATURES | 55" Signature Series True Outdoor All-Weather LCD-LED Television for permanent outdoor installation. |
| | Bright 55-inch Full-HD 1080p 120 Hz LCD-LED screen for improved outdoor viewing. |
| | Exterior designed to protect internal components from rain, dust, insects, humidity, and salt air. |
| | • Multi-fan airflow system keeps the unit cool and dry in temperatures up to 122 degrees F. |
| | • Ability to operate in cold weather (-24 degrees F). |
| | • RS232 serial control with discrete on, off, and input control (located in the cable- entry compartment). |
| | • Rear IR receiver (located in the cable-entry compartment). |
| | Innovative water-tight Cable Entry System seals out moisture and allows for easy hook-ups. |
| | • ASA outdoor rated high-impact resin exterior. |
| | • Weatherproof built-in 20W speakers. |
| | • Weatherproof remote control. |
| | Weatherproof control buttons. |
| | Remote Control Lock-Out prevents unauthorized users from changing the programming. |
| | |



MODEL 5565HD

| SCREEN | LCD SCREEN 55-inch diagonal TFT Active Matrix, LED Backlight RESOLUTION 1920 x 1080 Full-HD 1080p ASPECT RATIO 16:9 CONTRAST RATIO 1300:1 | FRAME RATE 120 Hz VIEWING ANGLE 176° x 176° RESPONSE TIME 12 milliseconds TV FORMATS 1080p, 1080i, 720p, 480p, 480i |
|---------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| CONNECTIONS | RF Antenna/CATV (ATSC/QAM/NTSC) x1 HDMI HDMI™ Input x2 VIDEO COMPOSITE S-Video x1 and Composite Video x1, L/R Audio Inputs x1 VIDEO COMPONENT YPbPr plus Stereo Audio x2 PC 15-pin D-sub VGA plus Stereo Audio | CONTROL SET RS232 Serial, Discrete IR Control, Concealed IR Window AUDIO OUT SPDIF Audio, Analog 1/8" headphone jack SPEAKERS 20 watt built-in speakers INPUT POWER 100-240 VAC, 50-60 Hz 2.0 A Max |
| TEMPERATURE TOLERANCES | OPERATING TEMP -24° to 122° F. (-31° to 50°C.) NON-OP. TEMP -24° to 140° F. (-31° to 60°C.) (OFF MODE WITH POWER APPLIED) The non-operating temperature feature re | equires power to be applied |
| PHYSICAL SPECS | ACCESSORIES INCLUDED Weatherproof remote control, outdoor dust cover EXTERIOR Outdoor rated ASA high-impact resin EXTERIOR COLORS Black, Silver, White TV DIMENSIONS 53.4"W x 33.8"H x 7.3"D TV WEIGHT 109.0 lbs. | SHIPPING DIMENSIONS 60"W x 46"H x 13"D SHIPPING WEIGHT 129.0 lbs. RESIDENTIAL WARRANTY Two year parts & labor COMMERCIAL WARRANTY Two year parts & labor |