



5 SERIES VENTILATION HOODS

Clear the Air



In a kitchen full of aromas, allow the scent of fresh food to emerge above the rest. Viking Professional Ventilation offers classic Viking appeal – heavy-duty, yet stylish, with new dimmable LED lighting and the ability to easily adjust the fan speed while cooking. Clear the air with Viking Professional Ventilation systems designed to complete your Viking kitchen.



12"H. Wall Hood*



18"H. Wall Hood*



18"H. Chimney Wall Hood



18"H. Chimney Island Hood

Built-In Custom Ventilator models available

*Wall hoods shown with optional duct cover



5 SERIES VENTILATION HOOD FEATURES

Heavy-Duty Professional Design

- Backlit LED knobs extend and illuminate to control lighting level and fan speed, then fully retract when not in use
- Seamless design provides a refined finish to your kitchen



Quiet, Efficient, and Maintenance-Free Ventilators*

- 460 CFM interior-power ventilator comes standard and quietly delivers powerful smoke and odor removal - 12"H. only
- Tough-box ventilator housing protects blower and quietly removes smoke and odor - 18"H. only
- Quietest hood and ventilator combination in the industry - 18"H. only
- Multi-speed ventilator control knob allows precise adjustment to desired fan speed
- Maintenance-free ventilators never need to be cleaned with the commercial-type hood filters doing the dirty work
- Cook with peace of mind as the built-in heat sensor activates the ventilator to full power if cooking temperatures reach uncomfortable levels

* Ventilators must be purchased separately for 18"H. Hoods and are available in internal, external, and in-line models

Bright LED Lighting

- Dimmable lighting controls provide custom illumination for enhanced surface cooking visibility
- Long-life LED light bulbs are energy efficient and easily replaceable
- Heat lamps conveniently keep food warm until ready to serve (not available on Island Hoods) - 18"H. only



12"H. Interior



18"H. Interior

Easy Maintenance and Clean-up

- Commercial-type baffle filters efficiently remove heat and grease vapors from the air
- Stainless steel dishwasher-safe filters are easily removed for quick cleaning
- Low-profile filter system reduces interior hood space, leaving less surface to clean
- Removable trough collects liquefied grease for convenient disposal - 18"H. only

Accessory Installation Products

- Duct covers
- Backsplashes
- Make-up air damper kits
- Recirculating hood conversion kits - 12"H. only
- Warming shelf panels (wall hoods) - 18"H. only
- Internal ventilator kits - 18"H. only
- Exterior power ventilator kits - 18"H. only
- In-line ventilator kits - 18"H. only
- Duct silencers - 18"H. only



Exclusive Finishes

- Available in Stainless Steel (SS), Black (BK), White (WH), Apple Red (AR), Burgundy (BU), Cinnamon (CN), Cobalt Blue (CB), Dijon (DJ), Graphite Gray (GG), Stone Gray (SG), Viking Blue (VB), and Wasabi (WS)

The Industry's Best and Most Comprehensive Warranty

- **3-year** full – complete product
- **90-day** full - cosmetic parts such as glass, painted items and decorative items
- **Lifetime** limited - stainless steel exterior
- **5-year** limited - ventilator motor



12"H. HOOD SPECIFICATIONS*

| VWH 12"H. Wall Hoods with Standard Ventilator | | |
|---|-------------------|-------------------|
| Description | VWH53012 | VWH53612 |
| Overall width | 29-7/8" (75.9 cm) | 35-7/8" (91.1 cm) |
| Overall depth | 21" (53.3 cm) | |
| Overall height | 12" (30.5 cm) | |
| Interior ventilator kit | 460 CFM Standard | |
| Interior duct size** | 7" (17.8 cm) | |
| Interior - Maximum amps | 4.9 | |
| Approximate shipping weight | 56 lbs. (25.2 kg) | 60 lbs. (27 kg) |

* Always refer to installation instructions included with product or visit vikingrange.com/specs for the most accurate cutouts and installation requirements.

** Disregard when using recirculating kits. 460 CFM blower is shipped with hood. Maximum duct run is 50 ft.

18"H. HOOD SPECIFICATIONS*

| VWH 18"H. Wall Hoods | | | | | |
|--------------------------|--------------------------|--------------------------|--------------------------|--------------------|--------------------|
| Description | VWH53048 | VWH53648 | VWH54248 | VWH54848 | VWH56048 |
| Overall/duct cover width | 29-7/8" (75.9 cm) | 35-7/8" (91.1 cm) | 41-7/8" (106.4 cm) | 47-7/8" (121.6 cm) | 59-7/8" (152.1 cm) |
| Overall depth | 24" (61.0 cm) | | | | |
| Overall height | 18" (45.7 cm) | | | | |
| Duct cover depth | 12" (30.5 cm) | | | | |
| Duct cover height | 12" (30.5 cm) | | | | |
| Heat lamps | 1 | 1 | 1 | 2 | 3 |
| Interior ventilator kits | VINV300/600/1200 | VINV300/600/1200 | VINV600/1200 | VINV1200* | VINV1200* |
| Exterior ventilator kits | DEV900/1200* | DEV900/1200* | DEV900/1200* | DEV1200*/1500** | DEV1200*/1500** |
| In-line ventilator kits | DIL1200 | DIL1200 | DIL1200 | DIL1200 | DIL1200 |
| Interior duct size | 7"/10" (17.8/25.4 cm) | 7"/10" (17.8/25.4 cm) | 7"/10" (17.8/25.4 cm) | 10" (25.4 cm) | 10" (25.4 cm) |
| Exterior duct size | 10" (24.5 cm) | | | | |
| Interior—Maximum amps | 4.2/5.2/8.2 | 4.2/5.2/8.2 | 5.2/8.2 | 10.8 | 10.8 |
| Exterior—Maximum amps | 8.0/5.3 | 8.0/5.3 | 8.0/5.3 | 7.8/8.5 | 7.8/8.5 |
| In-Line—Maximum amps | 5.3/7.2 | 5.3/7.2 | 5.3/7.2 | 9.6 | 10.0 |

| VCWH 18"H. Chimney Wall Hoods | | | | | |
|-------------------------------|--------------------------------|-------------------|--------------------|--------------------|--------------------|
| Description | VCWH53048 | VCWH53648 | VCWH54248 | VCWH54848 | VCWH56048 |
| Overall width | 29-7/8" (75.9 cm) | 35-7/8" (91.1 cm) | 41-7/8" (106.4 cm) | 47-7/8" (121.6 cm) | 59-7/8" (152.1 cm) |
| Overall depth | 24" (61.0 cm) | | | | |
| Overall height | 18" (45.7 cm) | | | | |
| Duct cover width | 12" (30.5 cm) | 12" (30.5 cm) | 12" (30.5 cm) | 18" (45.7 cm) | 24" (61.0 cm) |
| Duct cover depth | 12" (30.5 cm) | | | | |
| Duct cover height | 12" (30.5 cm) to 24" (61.0 cm) | | | | |
| Heat lamps | 1 | 1 | 1 | 2 | 3 |
| Interior ventilator kits | VINV300/600 | VINV300/600 | VINV600 | VINV1200** | VINV1200** |
| Exterior ventilator kits | DEV900/1200** | DEV900/1200** | DEV900/1200** | DEV1200**/1500*** | DEV1200**/1500*** |
| In-line ventilator kits | DIL1200 | DIL1200 | DIL1200 | DIL1200 | DIL1200 |
| Interior duct size | 7" (17.8 cm) | 7" (17.8 cm) | 7" (17.8 cm) | 10" (25.4 cm) | 10" (25.4 cm) |
| Exterior duct size | 10" (24.5 cm) | | | | |
| Interior—Maximum amps | 4.2/5.2 | 4.2/5.2 | 5.2 | 10.8 | 10.8 |
| Exterior—Maximum amps | 8.0/5.3 | 8.0/5.3 | 8.0/5.3 | 7.8/8.5 | 7.8/8.5 |
| In-Line—Maximum amps | 5.3/7.2 | 5.3/7.2 | 5.3/7.2 | 9.6 | 10.0 |

18"H. HOOD SPECIFICATIONS CONTINUED*

| VCIH 18"H. Chimney Island Hoods | | | | |
|---------------------------------|---|-----------------------|--------------------|--------------------|
| Description | VCIH53608 | VCIH54208 | VCIH55408 | VCIH56608 |
| Overall width | 35-7/8" (91.1 cm) | 41-7/8" (106.4 cm) | 53-7/8" (136.8 cm) | 65-7/8" (167.3 cm) |
| Overall depth | 30" (76.2 cm) | | | |
| Overall height | 18" (45.7 cm) | | | |
| Duct cover width | 12" (30.5 cm) | 12" (30.5 cm) | 18" (45.7 cm) | 24" (61.0 cm) |
| Duct cover depth | 12" (30.5 cm) | | | |
| Duct cover height | 12" (30.5 cm) or 24" (61.0 cm) or 36" (91.4 cm) | | | |
| Interior ventilator kits | VINV600 | VINV600 | VINV1200** | VINV1200** |
| Exterior ventilator kits | DEV900/1200** | DEV900/1200**/1500*** | DEV1200**/1500*** | DEV1200**/1500*** |
| In-line ventilator kits | DIL1200 | DIL1200 | DIL1200 | DIL1200 |
| Interior duct size | 7" (17.8 cm) | 7" (17.8 cm) | 10" (25.4 cm) | 10" (25.4 cm) |
| Exterior duct size | 10" (24.5 cm) | | | |
| Interior—Maximum amps | 4.2/5.2 | 5.2/8.2 | 8.9 | 9.3 |
| Exterior—Maximum amps | 7.4/4.7 | 7.4/4.7/5.5 | 5.6/6.4 | 6.4/7.4 |
| In-Line—Maximum amps | 4.7/6.5 | 3.9/5.7 | 7.4 | 7.4 |

| VBCV 18"H. Wall Custom Ventilator System | | | | |
|--|-----------------------|-----------------------|---------------------|---------------------|
| Description | VBCV53638 | VBCV54238 | VBCV54838 | VBCV56038 |
| Overall width | 33-7/16" (84.9 cm) | 39-7/16" (100.2 cm) | 45-7/16" (115.4 cm) | 57-7/16" (145.9 cm) |
| Overall depth | 21-7/16" (54.5 cm) | | | |
| Heat lamps | 1 | 1 | 2 | 3 |
| Interior ventilator kits | VINV300/600/1200** | VINV600/1200** | VINV1200** | VINV1200** |
| Exterior ventilator kits | DEV900/1200** | DEV900/1200** | DEV1200**/1500*** | DEV1200**/1500*** |
| In-Line ventilator kits | DIL1200 | DIL900/1200 | DIL1200 | DIL1200 |
| Interior duct size | 7"/10" (17.8/25.4 cm) | 7"/10" (17.8/25.4 cm) | 10" (25.4 cm) | 10" (25.4 cm) |
| Exterior duct size | 10" (25.4 cm) | | | |
| Interior—Maximum amps | 4.2/5.2 | 10.8 | 10.8 | 10.8 |
| Exterior—Maximum amps | 8.0/5.3 | 8.0/5.3 | 7.8/8.5 | 7.8/8.5 |
| In-Line—Maximum amps | 5.3/7.2 | 5.3/7.2 | 9.6 | 10.0 |

** A 1,200 CFM interior or exterior-power ventilator should be used when installed over range/rangetop with gas chargrill. Maximum duct run is 50 ft.

*** It is recommended that the 1,500 CFM ventilator be used with longer duct runs. Maximum duct run is 75 ft.

NOTE: Maximum amp rating for hoods includes recommended ventilator kit rating; All products must be hard wired 2-wire with ground. An interior or exterior-power ventilator kit must be purchased for installation with all 18"H. hoods.



For detailed product information, model numbers, or to request a quote call 1-888-845-4641 or visit vikingrange.com

F60295

*Always refer to installation instructions included with product or visit vikingrange.com/specs for the most accurate cutouts and installation requirements.

Viking Range, LLC products are sold under the Brigade brand exclusively in Canada.

