

Professional Cooktops

7x

Models available



Perfect Heat

Sealed Dual Flow Burners™ unique to DCS appliances, put you in control. The powerful burners—17,500BTU boil fast, yet you can also gently simmer sauces on every burner at 140°F.



Easy to Clean, Easy to Use

Sealed burners on an encapsulated cooking surface, the seamless design of the cooktop and a stainless steel finish make this cooking surface easy to clean. Full coverage, deep-platform style grates allow for easy sliding of larger pots and pans.



Professional Quality Griddle and Grill

Grill models feature even heat and reduced smoke output. Double-sided stainless steel grates drain fat away from cooking food. Heavyweight ¼" stainless steel griddles (up to 17" wide) and an electro-mechanical thermostat maintain an even temperature across the griddle surface.



Information at a Glance

The unique ergonomically designed metal dials offer complete control and at-a-glance confirmation of cooktop temperatures.



Grease Management System™ Grease Channeling Technology.

Grease drip-pan is accessible from the cooktop surface for quick removal and is dishwasher safe for easy cleaning. Double sided cast 304 grade stainless grates assists with better grease flow to help eliminate fats while cooking.

Professional Cooktops



	CPV-484GG	CPV-485GD	CPV-486GD	CPV-486GL	CPV-366	CPV-364GD	CPV-364GL
COOKTOP							
Power source	Gas	Gas	Gas	Gas	Gas	Gas	Gas
LP and Natural Gas Compatible	•	•	•	•	•	•	•
Sealed Cooking Surface	•	•	•	•	•	•	•
Sealed, Dual Flow Burners™	4	5	6	6	6	4	4
Grill Performance (BTU)	12,000			12,000			12,000
Griddle Performance (BTU)	18,000	25,000	18,000			18,000	
Grease Management System*	•			•		•	
BURNERS							
17,500 BTU Burners	2	3	4	4	4	2	2
12,500 BTU Burners	2	2	2	2	2	2	2
140°F Simmer Burners	4	5	6	6	6	4	4
RECOMMENDED VENTILATION							
VS48-48" Pro Wall Mount Vent Hood	•	•	•	•			
VS36-36" Pro Wall Mount Vent Hood					•	•	•
VS1236-36" Pro Wall Mount Vent Hood (1200 CFM)							•
ES36-36" E-Pro Vent Hood					•	•	
RECOMMENDED ACCESSORIES (OPTIONAL)							
Backguard BGCU-1236					•	•	•
Backguard BGCU-3036					•	•	•
Backguard BGCU-1248	•	•	•	•			
Backguard BGCU-3048	•	•	•	•			
RGP-Range Griddle Plate				•	•		•
POWER REQUIREMENTS							
120V/60Hz - 15A circuit	•	•	•	•	•	•	•
GAS REQUIREMENTS							
½NPT, min. 5/8" diameter flex line	•	•	•	•	•	•	•
NG Supply Pressure 6" to 9" W.C	•	•	•	•	•	•	•
LPG Supply Pressure 11" to 14" W.C	•	•	•	•	•	•	•
PRODUCT DIMENSIONS							
Height (in.)	8 ⁵ / ₁₆	8 ⁵ / ₁₆	8 ⁵ / ₁₆	8 ⁵ / ₁₆	8 ⁵ / ₁₆	8 ⁵ / ₁₆	8 ⁵ / ₁₆
Width (in.)	47 ⁷ / ₁₆	47 ⁷ / ₁₆	47 ⁷ / ₁₆	47 ⁷ / ₁₆	35 ⁷ / ₁₆	35 ⁷ / ₁₆	35 ⁷ / ₁₆
Depth (in.)	28	28	28	28	28	28	28
Stainless Steel Finish	•	•	•	•	•	•	•
WARRANTY							
Limited 2 Years Parts & Labor Warranty	•	•	•	•	•	•	•