



# **Signature Series**

HP48RR-S - 48" Refrigerator=Refrigerator



Indoor Models

Outdoor Models

\*Door models available with left or right hinge; see back page for available door styles



Refrigerator/Refrigerator HP48RR-S-3L-3R



Refrigerator/Refrigerator HP48RR-S-1L-1R

Refrigerator/Refrigerator HP48RR-S-5-5

- **General Signature Series Features** 
  - Zero-clearance hinging allows for abutment with surrounding cabinetry
  - Perlick's exclusive commercial-grade variable speed compressor
  - Front-vented, RAPIDcool forced-air refrigeration system
  - Commercial-grade stainless steel interior
  - *Industry Exclusive* convertible door design allows all doors the ability to be converted to wood overlay from stainless steel
  - Industry Exclusive adjustable, full-extension pull-out shelves (drawer models and beer dispensers excluded)

### **Refrigerator/Refrigerator Features**

- RR model has a single temperature zone throughout
- Includes (2) full-extension pull-out shelves in each zone for a total of four (4) shelves (drawer models excluded)
- Refrigerator temperature 30°- 42°F (factory set at 38°F)

- Stainless-steel ball-bearing glides provide smooth movement of shelves
- Low E, UV-coated glass provides industry leading insulation and protection.
- State-of-the-art digital control module
- Optional door locks and Industry-Exclusive drawer locks (factory installed)
- 12 cubic feet of capacity
- Industry Best Three-Year Warranty plus additional three years on sealed system

INNOVATION YOU CAN'T LIVE WITHOUT

Form No.HP48RR Rev. 08.02.2012

8300 W. Good Hope Rd. • Milwaukee, WI 53223 1-800-558-5592 • Fax: (414) 353-7069 • perlick.com Perlick is committed to continuous improvement. Therefore, we reserve the right to change specifications without warning.

## **Product Specifications**

### Available Indoor Models - 48" Refrigerator=Refrigerator **Overall Width** HP48RR-S 47-7/8" (121.60 cm.) 48" Refrigerator=Refrigerator **Overall Height** 34-1/4" (86.96 cm.) Available Outdoor Models - 48" Refrigerator=Refrigerator **Overall Depth** 24" (60.96 cm.) HP48RR-O 48" Refrigerator=Refrigerator **Opening Width** 48" (121.92 cm.) **Opening Height** 34-3/8" (87.31 cm.) **Refrigerator Door Options** 24" (60.96 cm.) **Opening Depth** 1 Solid Stainless Door (left or right hinge) **Refrigerated Volume** 12 cu. ft. 2 Solid Wood Overlay Door (left or right hinge) **Door Swing Clearance** 25" (63.50 cm.) minimum 3 Stainless Glass Door (left or right hinge) Electrical 115V, 60Hz., 1 Phase, 4 Wood Overlay Glass Door (left or right hinge) 2.3 amps 5 Solid Stainless Steel Drawers Plumbing None Required 6 Wood Overlay Drawers Annual Energy Usage 370 kWh/yr **Shipping Weight** 332 lbs (150.60 kg.) 50" Area in which al outlet must be locate - 12 1/4" --Power cord 8-1/4" off floor." YEA US 1 6 3/8 22 \*- Leg leveler can add 3/4" to these dimensions when fully extended. 1 1/4" Min 11 3/4 a corner to acheive 90 door swing 90° Swing required for pull-out shelf 24 15/16" clearance arance 25 7/16" Values may chan due to custom pull with a wood overlay door 25 7/16" Values may change due to custom pull with a wood overlay door. 24\* (with ±1/16" tolerance) 24' (with ±1/16" tolerance 18 1/8" 20 11/16 1 11/16" 1 11/16 1 11/16" **2** H P 5 5 5 5 5 5 5 2 2 2 2 2 2 3 3 3 2" Shel 2" Shel 26 9 26 9 26 5 1/4" 5 1/4\* 6 3/16" Lowest Ŧ \_2 1/4" Lowest 6 3/8" 11 3/4 - \*4" 50" Area in which al outlet must be located - 12 1/4" Power cord 8-1/4" off floor." \*- Leg leveler can add 3/4" to these dimensions when fully extended. 17 13/16" 17 13/16" 17 1 Inside drawe (Top & Botton Inside drawer (Top & Bottom 25 7/16\* Values may change due to custom pull with a wood overlay door. 1 3/8 25 7/16" Values may change due to custom pull with a wood overlay door 24' 24 47 7/8 (with +1/16" tole (with +1/16" tolera СÍ. 1 ю 1 1 9 3/16" Max product ht. 9 3/16" Max. product ht. 6 3/16" 6 3/16" - 17 1/4" - 17 1/4 Ŧ 10 3/4" Max. product ht. \*34 ł 8 3/8 10 3/4" Max. product ht. 6 3/4" - 10 1/ 6 3/16" - 17 1/4" -



8300 W. Good Hope Rd. • Milwaukee, WI 53223 1-800-558-5592 • Fax: (414) 353-7069 • perlick.com Perlick is committed to continuous improvement. Therefore, we reserve the right to change specifications without warning. Form No.HP48RR Rev. 08.02.2012