

Speed Queen® Multi-Housing

Micro Display Commercial Top Load Washer

Rear Control



BUILT FOR RELIABLE PERFORMANCE








- Dependable Eversmooth transmission
- Touch pad selector
- U.S. DOE compliance for energy and water efficiencies
- Extract speed of 710 RPMs spins clothes out drier
- 210° agitation stroke delivers superior washability
- Commercial-grade stainless steel or porcelain enamel washtub
- Automatic balancing suspension system

MICRO DISPLAY CONTROL

- Easy-to-read digital display
- Cycle programming flexibility
- Shows cycle time remaining
- Card and coin transactions



MICRO DISPLAY COMMERCIAL TOP LOAD WASHER SPECIFICATIONS

| MODELS and ACTIVATION {NOTE: Coin Box Sold Separately} | SWNBC2PP112TW01 | SWNBC2SP112TW01 | SWNBC2PP112TW02 | SWNBX2PP112TW01 | SWNBX2SP112TW01 | SWNBX2SP112TW02 | SWNBX2PP112TW02 |
|---|---|---|---|--|---|---|---|
| |  |  |  |  |  |  |  |
| | Coin "C" | Coin "C" | Coin "C" | Prep Card "Y" | Prep Card "Y" | Prep Coin "X" | Prep Coin "X" |
| Appearance | | | | | | | |
| Color | White | White | White | White | White | White | White |
| Control Panel Selection | Rear | Rear | Rear | Rear | Rear | Rear | Rear |
| Meter Case | Standard Capacity | Standard Capacity | High Capacity | -- | -- | Standard Capacity | High Capacity |
| Water and Energy Info | | | | | | | |
| Modified Energy Factor "MEF" ft³/kWh/cycle (Liters/kWh/cycle) | 1.70 (48.14) | 1.70 (48.14) | 1.70 (48.14) | 1.70 (48.14) | 1.70 (48.14) | 1.70 (48.14) | 1.70 (48.14) |
| Water Factor "WF" gal/ft³ (Liters/Liter/cycle) | 8.4 (1.12) | 8.4 (1.12) | 8.4 (1.12) | 8.4 (1.12) | 8.4 (1.12) | 8.4 (1.12) | 8.4 (1.12) |
| Water Consumption - gal (Liter) | 27.4 (103.6) | 27.4 (103.6) | 27.4 (103.6) | 27.4 (103.6) | 27.4 (103.6) | 27.4 (103.6) | 27.4 (103.6) |
| Water Consumption - gal (Liter) | 2.4 (9.0) | 2.4 (9.0) | 2.4 (9.0) | 2.4 (9.0) | 2.4 (9.0) | 2.4 (9.0) | 2.4 (9.0) |
| Technical Info | | | | | | | |
| Basket Volume - cu ft (liters): 3.26 (92.3) | Porcelain | Stainless | Porcelain | Porcelain | Stainless | Stainless | Porcelain |
| Net Weight - lb (kg) | 190 (86) | 190 (86) | 190 (86) | 190 (86) | 190 (86) | 190 (86) | 190 (86) |
| Shipping Weight - lb (kg) | 210 (95) | 210 (95) | 210 (95) | 210 (95) | 210 (95) | 210 (95) | 210 (95) |
| Electrical Requirements - 120/60/1 15 amp | Yes | Yes | Yes | Yes | Yes | Yes | Yes |
| Overall Dimensions WxDxH - in (mm): 25 5/8 (651) x 28 (711) x 43 (1092) | High Capacity: 25 5/8 (651) x 28 (711) x 43 7/8 (1114) | | | | | | |
| Cabinet Height - in (mm) | 36 (914) | 36 (914) | 36 (914) | 36 (914) | 36 (914) | 36 (914) | 36 (914) |
| Temperature - Hot, Warm, Cold | Yes | Yes | Yes | Yes | Yes | Yes | Yes |
| Cycles - Normal/Hot, Normal/Warm, Perm Press/Warm, Delicate/Cold | | | | | | | |
| Motor | 1/2 HP | 1/2 HP | 1/2 HP | 1/2 HP | 1/2 HP | 1/2 HP | 1/2 HP |
| Water Pressure PSI (Bar) - 20-120 (1.4-8.3) | Yes | Yes | Yes | Yes | Yes | Yes | Yes |
| Spin Speed - RPM (high 710, low 474) | 2 Speed | 2 Speed | 2 Speed | 2 Speed | 2 Speed | 2 Speed | 2 Speed |
| Performance/Features | | | | | | | |
| Manual Audits | Yes | Yes | Yes | Yes | Yes | Yes | Yes |
| Agency Approval | cULus | cULus | cULus | cULus | cULus | cULus | cULus |

For the most accurate information, the installation guide should be used for all design and construction purposes. Due to continuous product improvements, design and specifications subject to change without notice. The quality management system of Alliance Laundry Systems' Ripon facility has been registered to ISO9001:2008.

