

FS24L7PLUS



19.63" x 18.5" x 17.63" (H x W x D)

Compact commercially listed all-freezer, manual defrost with a lock and traceable thermometer

Highlights:

Commercially listed to NSF-7 standards

Compact size is ideal for countertop use

Factory installed lock provides security you can count on

Product Features:

Commercially approved	ETL-S listed to ANSI-NSF Standard 7 for use in commercial establishments
Compact dimensions	Ideal size for use on top of counters
Factory installed lock	Keyed security for a secure interior
-20° capable	Low temperature capability ideal for certain sensitive items
NIST calibrated thermometer	Thermometer provides external readout of current and high/low temperatures
One-piece interior liner	Seamless interior for easier cleanup
Manual defrost	Static cooling system for reduced temperature fluctuations
Removable shelf	Includes one wire shelf for easier storage
Adjustable thermostat	Dial thermostat located inside for easy temperature management

FS24L7PLUS Specifications:

Overview	
Height to Cabinet	19.63"
Height to Hinge Cap	20.0"
Width	18.5"
Depth	17.63"
Depth with door at 90°	34.5"
Capacity	1.4 cu.ft.
Defrost Type	Manual
Door	White
Cabinet	White
US Electrical Safety	ETL
Canadian Electrical Safety	ETL-C
Sanitation	ETL-S
Amps	0.8
Voltage/Frequency	115 V AC/60 Hz
Weight	35.0 lbs.
Shipping Weight	55.0 lbs.
Parts & Labor Warranty	1 Year
Compressor Warranty	5 Years
Freezer	
Door Swing	RHD
Reversible	Factory Reversible
Interior Height	14.38"
Interior Width	13.5"
Interior Depth	13.25"
Shelf Type	Wire
Shelf Qty	1
Thermostat Type	Dial
Refrigerant Type	R134a
Refrigerant Amount	1.5 oz.
Level Legs	2
Compressor Step Height	8.5"
Compressor Step Width	13.5"
Compressor Step Depth	6.0"

