PRODUCT SPECIFICATIONS



1224DWRSOD • 24" Outdoor Refrigerator Drawers • Outdoor Series





STAINLESS SOLID

PERFORMANCE	 Volume of 5.4 cu ft holds up to 98 bottles (12 oz) or 150 cans (12 oz) Digital Touch Pad Control Temperature range: 34°F - 45°F Passive cooling system
INTERIOR/EXTERIOR	 Black interior is illuminated with LED lighting Equipped with 2 full-extension robust stainless drawers 1 ¹/4" diameter stainless steel handles The lower drawer is large enough to fit 2 one-gallon containers with additional space for more storage Full stainless steel cabinet and drawers are deemed suitable for outdoor use by UL
INTEGRATION	 Unit is designed to be built-in or can be freestanding with the freestanding accessory kit Four independently adjustable leveling legs provide a precise undercounter fit

FEATURES & BENEFITS

MODEL DETAILS

Model	Voltage/Hz	Door Swing	Finish	Shipping Weight
U-1224DWRSOD-00A	115 / 60	Drawers	Stainless Solid	142 lb


ACCESSORIES

Model	Description	Finish	Shipping Weight
U-FSK-S	Freestanding Kit	Stainless	3 lb




Outdoor Series • 24" Outdoor Refrigerator Drawers • 1224DWRSOD

DIMENSIONS



CABINET CUT-OUT



INSTALLATION NOTES

Cutout includes the additional 1/4" width overall to ensure proper installation.

No additional clearance around sides, top or rear of unit is needed for ventilation.

SPECIFICATIONS

Model	1224DWRSOD	
Amps: Running	1.2	
Capacity: Bottle (12 oz)	98	
Capacity: Can (12 oz)	150	
Capacity: Volume (cu ft)	5.4	
Control Type	Digital Touch Pad	
Dimensions: Product Depth	23 ¼" / 591 mm	
Dimensions: Product Height	34 1/ 8" / 867 mm	
Dimensions: Product Width	24" / 610 mm	
Energy Consumption: Avg. Per Year	305 kWh	
ENERGY STAR	No	
Panel Width	23 ¾" / 603 mm	
Product Weight: Max	132 lb	
Refrigerant Type	R600a	
Sabbath (Star K Certified)	Yes	
Temperature Range	34°F - 45°F	

COOLING SYSTEM



ELECTRICAL REQUIREMENTS

This unit requires a grounded, polarized 115 VAC, 60 Hz, 15 A power supply (normal household current).





Please visit u-line.com to view this model's User Guide & Service Manual. All Specifications are subject to change without notice.

Deemed suitable for outdoor use by UL.