ZONEAIRE® SERIESPORTABLE AIR CONDITIONERS



FRIEDRICH 1883

COMFORT & CONVENIENCE

- 3-IN-1 SYSTEM: Air conditioner, dehumidifier and fan (P12B)
- 4-IN-1 SYSTEM: Air conditioner, heater, dehumidifier and fan (PH14B)
- Self-evaporative condensate system means no bucket to empty
- Condensate overflow protection
- 24-hour timer
- 3-speed fan
- Easy-access, washable antimicrobial filters
- Auto restart after power outage
- Built-in drain pump to remove condensate in heat pump mode (PH14B)
- Removes up to 72 pts./day when used as a dehumidifier

SPECIFICATIONS

| Model | | P12B | PH14B |
|----------------------------|--------------|-----------------------------|------------------|
| PERFORMANCE | | | |
| Cooling Capacity | Btu | 11600 | 13500 |
| Heating Capacity | Btu | _ | 10700 |
| Energy Efficiency Rating | EER | 8.8 | 9.5 |
| Coefficient of Performance | COP | _ | 2.8 |
| Air Movement | CFM | 235 | 250 |
| Moisture Removal | Pts/hr. | 6.0 | 6.0 |
| SPECIFICATIONS | | | |
| Refrigerant Type | | R410A | |
| Power Supply | Volts | 115 | |
| Rated Current | Cooling Amps | 10.5 | 10.8 |
| Rated Current | Heating Amps | _ | 10.8 |
| Watts | | 1318 | 1421 / 1120 |
| Dimensions (Inches) | WxHxD | 19 1/2" x 33 5/8" x 15 1/2" | |
| Weight (Net/Shipping) | Lbs. | 72 / 90 | 78 / 95 |
| Carton Dimensions (Inches) | WxHxD | 20 7/8" x 43 | 3 1/8" x 16 3/4" |

| | Circuit Rating | | | Power |
|-------------|----------------|-----------|-------------|--------|
| | Breaker or | Plug Face | Wall Outlet | Cord |
| Model | T-D Fuse | (NEMA#) | Appearance | Length |
| P12B, PH14B | 125V - 15A | 5 - 15P | | 6 ft. |

EASY INSTALLATION

- Quick installation Snap-in hoses and 115v operation mean quick start-up and cooling.
- Easy-roll casters for portability
- All installation accessories included
- Window kit fits vertical and horizontal standard windows and some casement windows
- 6 ft. long power cord

INSTALLATION KIT- Two flexible, heavy duty hoses extend from 24" to 60".

The hoses can be vented through a window with the window slider panel, or through a wall opening to the outside.



NOTE: Window slider panel can be trimmed to fit a smaller opening.



WINDOW KITS INCLUDED All models include easy-to-install window kits to vent the unit to the outside.

Due to continuing research in new energy-saving technology, specifications are subject to change without notice.

NOTE: Air conditioners will provide cooling at outdoor temperatures down to 41° F and

PH14B heat pump will provide heating at outdoor temperatures down to 14° F with single hose installation.





Friedrich Air Conditioning Co. I 10001 Reunion Place, Suite 500 | San Antonio, TX 78216 | 877.599.5665 | www.friedrich.com

BRO_PAC_COMM_2018 Printed in USA