



FRIEDRICH

1 8 8 3

ZoneAire® Series

PORTABLE AIR CONDITIONERS

Portable heating & cooling solutions



THE EXPERTS IN ROOM AIR CONDITIONING


FEATURES AND INSTALLATION

Comfort & Convenience

- 3-IN-1 SYSTEM: Air conditioner, dehumidifier and fan (P12B)
- 4-IN-1 SYSTEM: Air conditioner, heater, dehumidifier and fan (PH14B)
- Self-evaporative condensate system means no bucket to empty
- Condensate overflow protection
- 24-hour timer
- 3-speed fan
- Easy-access, washable antimicrobial filters
- Auto restart after power outage
- Built-in drain pump to remove condensate in heat pump mode (PH14B)
- Removes up to 72 pts./day when used as a dehumidifier

SPECIFICATIONS

Model		P12B	PH14B
PERFORMANCE			
Cooling Capacity	Btu	11600	13500
Heating Capacity	Btu	—	10700
Energy Efficiency Rating	EER	8.8	9.5
Coefficient of Performance	COP	—	2.8
Air Movement	CFM	235	250
Moisture Removal	Pts/hr.	6.0	6.0
SPECIFICATIONS			
Refrigerant Type		R410A	
Power Supply	Volts	115	
Rated Current	Cooling Amps	10.5	10.8
Rated Current	Heating Amps	—	10.8
Watts		1318	1421 / 1120
Dimensions (Inches)	W x H x D	19 1/2 x 33 5/8 x 15 1/2	
Weight (Net/Shipping)	Lbs.	72 / 90	78 / 95
Carton Dimensions (Inches)	W x H x D	20 7/8 x 43 1/8 x 16 3/4	

Model	Circuit Rating Breaker or T-D Fuse	Plug Face (NEMA#)	Wall Outlet Appearance	Power cord length
P12B, PH14B	125V - 15A	5 - 15P		6 ft.

Installation Features

- Quick installation - Snap-in hoses and 115v operation mean quick start-up and cooling.
- Easy-roll casters for portability
- All installation accessories included
- Window kit fits vertical and horizontal standard windows and some casement windows
- 6 ft. long power cord

INSTALLATION KIT- Two flexible, heavy duty hoses extend from 24" to 60".

The hoses can be vented through a window with the window slider panel, or through a wall opening to the outside.



NOTE: Window slider panel can be trimmed to fit a smaller opening.



WINDOW KITS INCLUDED

All models include easy-to-install window kits to vent the unit to the outside.

Due to continuing research in new energy-saving technology, specifications are subject to change without notice.

NOTE: Air conditioners will provide cooling at outdoor temperatures down to 41° F and PH14B heat pump will provide heating at outdoor temperatures down to 14° F with single hose installation.



Friedrich Air Conditioning Co. | 10001 Reunion Place, Suite 500 | San Antonio, TX 78216 | 877.599.5665 | www.friedrich.com