## Portable Air Conditioners



## ZoneAire® Series

Complete line of portable heating & cooling solutions





Quick Installation Fast Cooling Easy Storage

#### ZoneAire®

# Dual hose portables provide up to 40% faster cooling. Efficient heat pump model cools & heats.

#### **Comfort & Convenience**

- 3-IN-1 SYSTEM: Air conditioner, dehumidifier and fan (P12B)
- 4-IN-1 SYSTEM: Air conditioner, heater, dehumidifier and fan (PH14B)
- Self-evaporative condensate system means no bucket to empty
- Condensate overflow protectionthe unit will automatically shut off if tank should become full
- 24-hour timer
- 3-speed fan
- Easy-access, washable antimicrobial filters
- Auto restart after power outage
- Built-in drain pump to remove condensate in heat pump mode (PH14B)
- Removes up to 72 pts./day when used as a dehumidifier

#### Installation Features

- Quick installation Snap-in hoses and 115v operation mean quick start-up and cooling
- Easy-roll casters for portability
- All installation accessories included
- Window kit fits vertical and horizontal standard windows and some casement windows
- 6 ft. long power cord



Use remote to select MODE, FAN SPEED, adjust TEM-PERATURE and set the TIMER.



WINDOW KITS INCLUDED All models include easy-to-install window kits to vent the unit to the outside.

### Best choice for total room cooling

#### P12B COOLING

COOLING 11600 Btu 8.8 EER

#### **PH14B**

C00LING 13500 Btu **9.5 EER** HEATING 10700 Btu **2.8 COP** 



#### PORTABLE MODEL COMPARISON

	ZoneAire		ZoneAire Compact	
	DUAL HOSE		SINGLE HOSE	
Feature	P12B	PH14B	P08S	P10S
Heat pump model	N	Υ	N	N
Built-in drain pump	N	Υ	N	N
Condensate overflow protection- Auto shutoff	Υ	Υ	N	N
Auto restart after power outage	Υ	Υ	Y	Υ
Built-in hose & power cord storage	N	N	Y	Υ
Easy-roll casters	Y	Υ	Y	Υ
Window kit included	Υ	Υ	Υ	Υ

### ZoneAire® Compact

# Small and compact single hose portables for fast setup and easy storage.

#### Comfort & Convenience

- 3-in-1 system: Air conditioner, dehumidifier and heater
- One side offers cooling and the other creates heat. Simply turn the unit around and hook the exclusive 'heat clip' for bonus heat option
- Super portability with built-in hose storage compartment underneath the unit
- Easy-access, washable antimicrobial dual filters
- 4-speed fan with Auto setting that maintains your ideal temperature
- 24-hr. timer for both cooling and dehumidification
- · Auto restart after power outage
- LCD remote control
- Unique Sleep Control function increases temperature 2 degrees every 4 hours

#### Installation Features

- Quick installation Snap-in hoses and 115v operation mean quick start-up and cooling
- Easy-roll casters for portability
- Small footprint, takes up minimal space only 17" wide
- · All installation accessories included
- 7 ft. long power cord



Use remote to select MODE, FAN SPEED, adjust TEM-PERATURE and set the TIMER.

#### ZoneAire® and ZoneAire® Compact Applications

- Supplemental or emergency cooling or heating anywhere
- Computer rooms
- Guard buildings
- Construction trailers/RVs
- Workshops and garages
- · Home offices
- Dorm rooms
- Bedrooms, attics and basements
- Sunrooms/ enclosed patios

## Best choice for spot cooling

#### **P08S**

COOLING 8000 Btu 8.3 EER

#### P10S

COOLING 10000 Btu **8.4 EER** 



## HEAT CLIP



#### **Bonus Heat**

One side offers cooling-simply turn the unit around and apply the exclusive 'heat clip' and attach hose for bonus heat option

#### IDEAL FOR AREAS WITH ADDED HEAT LOADS

You can quickly set up supplemental or emergency cooling for computer rooms.



#### INSTALLATION

#### ZoneAire® Installation Kit

INSTALLATION KIT- Two flexible, heavy duty hoses extend from 24" to 60". The hoses can be vented through a window or through a wall opening to the outside.

WINDOW SLIDER KIT (Included)



Fits HORIZONTAL or VERTICAL WINDOWS WINDOW OPENING:

Minimum: 26"\* Maximum: 46"

#### **ZoneAire® Compact Installation Kit**

INSTALLATION KIT- One flexible, heavy duty hose extends from 8" to 46". The hose can be vented through a window or through a wall opening to the outside.

WINDOW SLIDER KIT (Included)



Fits HORIZONTAL or VERTICAL WINDOWS WINDOW OPENING:

Minimum: 24 1/2"\* Maximum: 46"

#### **SPECIFICATIONS**

		Single hose compact		Dual hose	
Model		P08S	P10S	P12B	PH14B
PERFORMANCE					
Cooling Capacity	Btu	8000	10000	11600	13500
Heating Capacity	Btu	8300	10300	_	10700
Energy Efficiency Rating	EER	8.3	8.4	8.8	9.5
Coefficient of Performance	COP	_	_	_	2.8
Air Movement	CFM	212	247	235	250
Moisture Removal	Pts/hr.	3.5	4.4	6.0	6.0
Refrigerant Type		R410-A			
Power Supply	Volts	115			
Rated Current	Cooling Amps	9.0	11.0	11.5	10.8
Rated Current	Heating Amps	_	_	_	10.8
Watts		964	1190	1318	1421 / 1120
Dimensions (Inches)	WxHxD	17 x 25 <sup>1</sup>	/4 <b>x 11</b> <sup>1</sup> /2	19 <sup>1</sup> / <sub>2</sub> x 33	3 <sup>1</sup> /2 x 15 <sup>1</sup> /2
Weight (Net/Shipping)	Lbs.	53 / 57	57 / 62	72 / 90	78 / 95
Carton Dimensions (Inches)	WxHxD	18 x 26	x12 <sup>1</sup> / <sub>2</sub>	20 <sup>7</sup> /8 x 4	3 <sup>1</sup> /8 x 16 <sup>3</sup> /4

Model	Circuit Rating Breaker or T-D Fuse	Plug Face (NEMA#)	Wall Outlet Appearance	Power cord length
P08S, P10S,	125V - 15A	5 - 15P		7 ft.
P12B, PH14B	125V - 15A	5 - 15P		6 ft.



Due to continuing research in new energy-saving technology, specifications are subject to change without notice.

NOTE: Air conditioners will provide cooling at outdoor temperatures down to 41° F and PH14B heat pump will provide heating at outdoor temperatures down to 14° F with single hose installation.



Friedrich Air Conditioning Co. | 10001 Reunion Place, Suite 500 | San Antonio, TX 78216 | 877.599.5665 | www.friedrich.com

BRO\_PAC\_RTL\_2016 Printed in USA

<sup>\*</sup> Window slider kit can be trimmed to fit a smaller opening.

<sup>\*</sup> Window slider kit can be trimmed to fit a smaller opening.