



#### Color Variants

AR401740  
Stainless steel  
665 CFM

#### Installation Accessories

AD702052  
Telescopic wall-duct  
ø 8" round

AR401740  
400 series blower  
Stainless steel  
665 CFM  
Outside wall mounting  
Air extraction

Maximum output for downdraft ventilation and motorless hoods  
Outside installation allows lower noise level in the kitchen  
To be combined with motorless hoods or downdrafts.

#### Output

665 CFM

#### Features

Complete stainless steel housing.  
Duct connections air intake: 1 x Ø 8" round.

#### Planning notes

When installing a ventilation hood with air extraction mode and a chimney-vented fireplace, the hood's power supply line needs a suitable safety switch.  
Roof installation with roof installation set AD 401 910 and telescopic wall duct AD 702 052 in slanted roofs with angle of minimal 10 °.  
For maximum duct lengths use Gaggenau flat rectangular ducts AD 8... or Naber-System Compair flow. Other flat ducts are not permitted!  
For noise optimisation, use the silencer SD 011 050.

#### Rating

Fan output NO\_FEATURE.  
Connecting cable 41 1/3"  
Performance output level 3/4:  
Air output according to EN 61591.  
Sound power and sound pressure depending on built-in situation.  
For the characteristics of each output level with/without intensive mode please refer to the table with the respective motorless ventilation products.

#### Product Features

#### Product Description

Product group  
Accessory  
Brand  
Gaggenau  
Product name / series name  
SKU  
AR401740  
Internal article number  
AR401740  
EAN code  
4242006207397  
Product packaging dimensions (HxWxD) (in)  
Net weight (lbs)  
34  
Gross weight (lbs)  
38  
Quantity per packing unit  
Standard number of units per pallet  
UPC code  
825225897866  
Name of product image  
MCSA043418\_AR401130\_def.jpg

2017-07-07

Page 1

AR401740  
400 series blower  
Stainless steel  
665 CFM  
Outside wall mounting  
Air extraction  
2017-07-07  
Page 2

