

Color Variants DF281760 fully integrated Width 24 " (61 cm)

### Included accessories

Installation Accessories

1 x baking tray spray head. 1 x GN container insert.

DA020110 Stainless steel trim kit for tall tub dishwashers DA021000 Folding hinge DA231110 Stainless steel-backed full glass door panel for tall tub dishwashers, handle included GH045010 Handle bar with 2 mounts, stainless steel, length 7 11/16", drilling distance 16 13/16", for custom panel. GZ010011

Extension for inlet and outlet (78" long)

Dishwasher	
fully integrated	
Width 24 " (61 cm)	
Appliance height 86.7 cm / 34 1	/8 "

8 programs with aqua sensor and 4 cycle options such as Power. Intensive, Half Load and Extra Dry Flexible rack system with smooth running rails on all levels and a softclosing system of the upper and lower rack TFT display for intuitive operation of all functions Remaining time projection onto the kitchen floor Bright interior lighting Push-to-open function for a seamless integration into handleless furniture fronts Very quiet: 40 dB Aqua stop **ENERGY STAR®** qualified

Operation TFT display indicating remaining or end time, refill for salt and rinsing agent, inflow of water. Touch key operation. Information key with use indications. Sanitized indicator in the control panel. Delayed start timer up to 24 hours. Visual and acoustic end of program indicator. Remaining time projection.

### **Technical features**

Bright interior lighting. Glass protection. Aqua sensor. Load sensor. Automatic detergent function. Regeneration electronics. Flow-through water heater. Triple filter system, self-cleaning. Soft lock. Aqua stop.

#### Programs

8 programs: Auto 113 °F - 122 °F. Auto 130 °F - 150 °F. Auto 150 °F - 160 °F. Standard Eco 122 °F - 131 °F. Wash and Dry. Quick Wash 113 °F (29 min.). Glass Care 122 °F. Pre-rinse. 4 cycle options: Intensive. Power. Half Load. Extra Dry.

# Features

Flexible rack system with smooth running rails on all levels and a softclosing system on the upper and lower rack. 3rd rack for cutlery. Upper rack: Over extension. Rackmatic with 3 levels, adjustable in height up to 2". 6 folding tines. 4 folding racks. 2 glass support bars. Lower rack: 8 folding tines. 2 folding racks. Dividable glass support. Cutlery basket. Maximum dish sizes (upper/lower basket) 9"/11", 8"/12" or 7"/13" respectively. 13 place setting capacity.

**Product Features** Watts (W) 1300 Current (A) Volts (V) 120 Frequency (Hz) 60 Power Cord Length 47 1/4' Minimum Water Pressure (lb/sin) 7.0 Length inlet hose (in) 55 1/8' Length outlet hose (in) 55 1/8 Overall appliance dimensions (HxWxD) (in) 34 1/8 " x 23 9/16 " x 21 5/8 " Required cutout size (HxWxD) (in) 34 1/8 " x 24 " x 24 Adjustable feet

Consumption and connection features Number of wash cycles

# Number of options

Yes

Third Rack 3rd Rack 2.1

Tub material Stainless steel

Concealed heating element Yes Leak protection system

24/7 Aqua Stop Plus Five-level wash

Yes Water softener Yes

ChildLock Total annual energy consumption (kWh) 259

Energy Efficiency Class Tier 1

Energy Star® qualified

Total annual energy consumption (kWh) 623.5 Total annual water consumption (g)

624 Number of place settings

13 2016-10-07

Page 1

Maximum glass loading capacity 23 wine glasses.

## Consumption data

Total annual energy consumption 259 kwh. Water usage 2.5 gallons Noise level 40 dB.

## Planning notes

Height-adjustable feet. Appliance toe kick recess 3 15/16". To display the remaining time projection, a minimum toe kick protrusion is required (1 9/16" + thickness of the furniture front). The maximum toe kick height must be reduced by 1 3/16" to provide an optimal display of the remaining time projection. Rear feet adjustable at front. Door weight up to 22 lbs. Door panel dimension dependent on toe kick height of kitchen cabinets. Installation and usage also with furniture handle possible. The push-toopen function remains active. Ventilation openings required when installed as a tall unit. Connection to hot or cold water possible. Water connection with 3/4" screw

Water connection with 3/4" screw gland.

## Rating

Total rating 1.3 kW. Total Amps: 12 A. 120 V / 60 Hz Connecting cable 47 1/4" plugable.



DF281760	
Dishwasher	
fully integrated	
Width 24 " (61 cm)	
Appliance height 86.7 cm / 34 1/	/8 "
2016-10-07	
Page 2	

Tall Tub dishwasher (341/8" (86.7 cm)).



