



Color Variants

AI280720
Stainless steel
Width 48"

Optional accessories

KF001010
Activated charcoal filter

AI280720
Island hood
Stainless steel
Width 48"
Air extraction/recirculation

- Coanda effect on both sides leads to highly efficient extraction, even on lowest power level
- Air extraction or recirculation system
- Dimmable Soft-Light
- Operation from both sides
- Unobstructed air flow. Maximum air output 400 CFM.

Features

Control panel on both sides.
3 electronically controlled output levels.
Intensive mode with ongoing Coanda effect.
Interval ventilation.
Delayed shut-off function
Grease filter saturation indication by flashing light
Cartridge-type filter, dishwasher-safe.
Fully illuminated surface with compact fluorescent tube 2 x 36 W and dimmable Soft-Light.

Planning notes

When installing a ventilation hood with air extraction mode and a chimney-vented fireplace, the hood's power supply line needs a suitable safety switch.
A large drop in output and significantly increased noise can be expected in the air recirculation mode in case of ventilation hoods with a very high air output.
Vario cooktops with intensive production of vapours like VR/VP/VF should be placed in the middle beneath the cooker hood (in this case air recirculation is not recommended).
Clearance above gas appliances min. 30".
Clearance above electric appliances min. 30".
Side outlet possible no lower than 22 4/5" from the bottom edge of the hood (pipe middle).
Plan the socket concealed behind ventilation duct.
Weight 90- 100 lb.
Recommendation for stainless steel parts positioned nearby that have to be welded and polished: brushed grain 280.
Surfaces: Stainless steel 1.4016, ground and brushed IIC.
The dimensions of the air ducts refer to a distance of 63" from the floor to the bottom edge of the hood.
Convert for other installation heights: Worktop height + minimum clearance + hood with duct cover.

Rating

Total connected load 335 W.
Connecting cable 30" with plug.

Product Features

Operating Mode
Convertible: Ducted / Recirculating
Number of speed settings
3-stage
Delay Shut off modes
10
Silence level (dBA)
Required accessories
Optional accessories
KF001010
Number of lights
2
Type of lamps used
Fluorescent
Total power of the lamps (W)
72
Grease filter material
Washable stainless steel
Grease filter type
Multilayer cassette
Clean filter reminders
Electronic

Consumption and connection features

UPC code
825225869177

Material
Stainless steel

Watts (W)
335

Current (A)

Volts (V)
120

Frequency (Hz)
60

Approval certificates
ETL

Power cord length (in)

Plug type
120V-3 prong

Overall appliance dimensions (HxWxD) (in)
26 3/8 " -54 5/16 / 33 1/16 " - 54 5/16 x 47 3/16 x 27 9/16

Product packaging dimensions (HxWxD) (in)
27.16 x 30.70 x 51.77

Height of the chimney (in)

Vertical rise height

Required distance above cooktop/ranges

Net weight (lbs)
94

Gross weight (lbs)
115

Adjustable feet

Motor location

Maximum CFM

Diameter of air duct (in) top

Diameter of air duct (in) back

Discharge direction

No-return airflow flap
No

2013-04-22

Page 1