



#### Color Variants

AW200792  
Stainless Steel  
Width 36", depth 22"

#### Optional accessories

KF001010  
Activated charcoal filter

#### AW200792

Wall-mounted hood

Stainless Steel

Width 36", depth 22"

Air extraction/recirculation

- Classic Gaggenau design
- Air extraction or recirculation system
- High performance and minimal sound

#### Features

3 electronically controlled output levels. Intensive mode. Interval ventilation. Delayed shut-off function. Grease filter saturation indication by flashing light. Cartridge-type filter, dishwasher-safe. Dimmable halogen Soft-Light 3 x 20 W.

#### Planning notes

For calculating the exhaust air line go to Rodun online at [www.gaggenau.com](http://www.gaggenau.com). For maximum duct lengths use Gaggenau flat rectangular ducts AD 8... or Naber-System Compair flow. Other flat ducts are not permitted!

When installing a ventilation hood with air extraction mode and a chimney-vented fireplace, the hood's power supply line needs a suitable safety switch.

A large drop in output and significantly increased noise can be expected in the air recirculation mode in case of ventilation hoods with a very high air output.

Vario cooktops with intensive production of vapours like VR/VP/VF should be placed in the middle beneath the cooker hood (in this case air recirculation is not recommended). Clearance above gas appliances min. 30".

Clearance above electric appliances min. 30".

Side outlet possible no lower than 22" from the bottom edge of the hood (pipe middle).

Fit the socket concealed behind ventilation duct.

Weight 64 - 73 lb.

Recommendation for stainless steel parts positioned nearby that have to be welded and polished: brushed grain 280.

Surfaces: Stainless steel 1.4016, ground and brushed IIIC.

The dimensions of the air ducts refer to a distance of 63" from the floor to the bottom edge of the hood.

Convert for other installation heights: Worktop height + minimum clearance + hood with duct cover.

#### Rating

Total connected load 220 W. Connecting cable 30" with plug.

#### Product Features

Operating Mode

Convertible: Ducted / Recirculating

Number of speed settings

3-stage

Delay Shut off modes

10

Silence level (dBA)

Required accessories

Optional accessories

KF001010

Number of lights

3

Type of lamps used

Halogen

Total power of the lamps (W)

60

Grease filter material

Washable stainless steel

Grease filter type

Multilayer cassette

Clean filter reminders

Electronic

#### Consumption and connection features

UPC code

825225851745

Material

Stainless steel

Watts (W)

220

Current (A)

Volts (V)

120

Frequency (Hz)

60

Approval certificates

Power cord length (in)

59 "

Plug type

Overall appliance dimensions (HxWxD) (in)

25 9/16 " - 56 3/16 " / 29 7/8 " - 55 7/8 " x 35 5/16 " x 22 "

Product packaging dimensions

(HxWxD) (in)

28.34 x 39.76 x 25.98

Height of the chimney (in)

21 5/8 " - 52 5/16 " / 26 " - 52 5/16 "

Vertical rise height

Required distance above cooktop/ranges

Net weight (lbs)

44

Gross weight (lbs)

62

Adjustable feet

Motor location

Maximum CFM

Diameter of air duct (in) top

6

Diameter of air duct (in) back

Discharge direction

No-return airflow flap

No

2013-04-22

Page 1

