



Color Variants

BO250611
Stainless steel-backed full glass door
Width 24" (60 cm)

Included accessories

1 x grill tub.
1 x enamel baking tray.
suit. pyrol. clean..
1 x grill shelf.
1 x pluggable meat probe.

Optional accessories

BA016103
Pull-out system
BA026113
Baking tray, enameled
BA036103
Wire rack, chromium-plated
BA046113
Glass tray
BA056113
Heating element for baking stone and cast-iron roaster
BA056133
Baking stone
BA226103
Broil pan, enameled
BS020002
Pizza peel, additional set of 2
GN340230
Non-stick aluminum cast-iron roaster

Product Variants

BO251611
200 series oven
Stainless steel-backed full glass door
Width 24" (60 cm)
Left-hinged

BO250611

Oven 200 series
Stainless steel-backed full glass door
Width 24" (60 cm)
Right-hinged

- Pyrolytic self-cleaning
- Universal heating system with 12 heating modes, meat probe and baking stone option.
- Electronic precision temperature control from 85° F - 550° F.
- Net volume 3.6 cu. ft.

Operation

LCD function display with digital clock.
Timer functions: cooking time, shut off time, short-term timer, stop watch, Sabbath mode.
Menu settings.
Actual temperature display.
Super-Quick preheating.
Rotary knob and touch key operation.

Features

Meat probe with automatic shut-off function.
Baking stone outlet.
Roasting function.
60 W halogen top light.
10 W halogen light on the side.
Enamel wire racks on the side with 4 rack levels, pyrolysis-safe.
Side-opening door opens up to 180° angle.

Safety

Thermally insulated door with four-fold glazing.
Child lock.
Safety lock.
Cooled housing with temperature protection.

Cleaning

Pyrolytic self-cleaning.
Gaggenau Clean-Enamel.
Heated air cleaning catalyst.

Planning notes

Please read the installation details regarding air ducting on page 9/10 of the M&D.
Door hinge not reversible.
The front of the appliance extends 1 7/8" from the cabinet front.
The outer edge of the door handle extends 3 11/16" from the cabinet front.
Consider the overhang, incl. the door handle, when planning to open drawers next to the appliance.
Plan a gap of at least 3/16" between the appliance and adjacent cabinets.
When planning a corner solution, pay attention to the 90° door opening angle.
To achieve the 21 5/8" installation depth, the connecting cable needs to follow the slanted edge on the lower right hand corner of the housing.
Plan a power outlet outside of the cut-out niche.
Plan for a connecting cable.

Rating

Total rating 3.0 kW.
Total Amps: 15 A
208 / 220 - 240 V / 60 Hz

Product Features

Cooking method first cavity
,, , , Bake, Defrost, Full width grill, Hot air and 1/1 bottom heating, Max Convection Broil, Proof, Top heat, True Convection

Cleaning system - cavity 1
Self Clean

Interior Lights - cavity 1
2

Telescopic rack
Accessory

Timer settings
Alarm, Off, On, timer

Included accessories
1 x grill tub, 1 x enamel baking tray, suit. pyrol. clean., 1 x grill shelf, 1 x pluggable meat probe

Bake Element Wattages cavity 1 (W)
1300

Broil Element Wattages cavity 1 (W)
3000

Convection Element Wattages cavity 1 (W)
2100

Microwave Wattages (W)

Drawer wattage (W)

Consumption and connection features

UPC code
825225859635

Product color
Stainless steel

Alternative colors available
BO250631

Energy source
Electric

Watts (W)
3030

Current (A)
15; 17

Volts (V)
208/220-240

Frequency (Hz)
60

Approval certificates
ETL

Power cord length (in)
59

Plug type
Fixed connection, No plug

Required cutout size (HxWxD) (in)
23 1/4 " x 22 1/16 " x 21 5/8 "

Product packaging dimensions (HxWxD) (in)
30.70 x 26.77 x 29.92

Net weight (lbs)
129

Gross weight (lbs)
140

2013-04-22

Page 1

