



Color Variants

BO451610
Stainless steel-backed full glass door
Width 24" (60 cm)

Included accessories

1 x enamel baking tray.
suit. pyrol. clean..
1 x grill shelf.
1 x grill tub with grid.
1 x pluggable meat probe.

Optional accessories

BA016103
Pull-out system
BA026113
Baking tray, enameled
BA036103
Wire rack, chromium-plated
BA046113
Glass tray
BA056113
Heating element for baking stone and cast-iron roaster
BA056133
Baking stone
BA226103
Broil pan, enameled
BS020002
Pizza peel, additional set of 2
GN340230
Non-stick aluminum cast-iron roaster

Product Variants

BO450610
400 series single oven
Stainless steel-backed full glass door
Width 24" (60 cm)
Right-hinged
controls on top

BO451610
400 series single oven
Stainless steel-backed full glass door
Width 24" (60 cm)
Left-hinged
controls on top

- Handleless door / automatic door opening
- Pyrolytic self-cleaning
- Universal heating system with 13 heating modes, with meat probe and baking stone operation
- TFT touch display
- Electronic precision temperature control from 85° F - 550° F.
- 3.2 cu.ft. net volume

Cooking modes

Convection.
Economy convection.
Top + bottom heat.
Top heat.
Bottom heat.
Convection+ bottom heat.
Convection broiling.
Broiling.
Economy broiling.
Baking stone operation.
Roaster operation.
Dough proofing.
Defrosting.

Operation

Automatic door opening.
Rotary knobs and TFT touch display operation.
Clear text display in 25 languages.
Option to save individual recipes (incl. meat probe)
Information key with use indicators.
Side-opening door opens up to 180° angle.

Features

Meat probe with automatic shut-off.
Baking stone outlet.
Actual temperature display.
Super-quick preheating.
Timer functions: cooking time, switch-off time, short-term timer, stopwatch, Sabbath mode.
60 W halogen top light.
10 W halogen light on the side.
Enamel wire racks on the side with 5 rack levels, pyrolytic-safe.

Safety

Thermally insulated door with quadruple glazing.
Child lock.
Safety lock.
Cooled housing with temperature protection.

Cleaning

Pyrolytic self-cleaning.
Gaggenau Clean-Enamel.
Heated air cleaning catalyst.

Planning notes

Door hinge not reversible.
The front of the appliance extends 1 7/8" from the cabinet front.
When handle (optional accessory) is installed, the outer edge of the door handle extends 3 11/16" (94mm) from the cabinet front.
Consider the overhang, incl. the door handle where applicable, when planning to open drawers next to the appliance. Plan a gap of at least 3/16" between the appliance and adjacent cabinets.
When planning a corner solution, pay attention to the 90° door opening angle.
To achieve the 21 5/8" installation depth, the connecting cable needs to follow the slanted edge on the lower

Product Features

Cooking method primary cavity
Bake, Baking stone function, Bottom heat, Defrost, Full width grill, Half width grill, Hot air and 1/1 bottom heating, Hot Air-Eco, Max Convection Broil, Proof, Roaster function, Sabbath function, Top heat, True Convection

Cleaning system - primary cavity
Self Clean

Interior Lights - primary cavity
2

Pull-out system
Accessory

Timer settings
Alarm, Off, On, timer

Included accessories
1 x enamel baking tray, suit. pyrol. clean., 1 x grill shelf, 1 x grill tub with grid, 1 x pluggable meat probe

Bake Element Wattages primary cavity (W)
1300

Broil Element Wattages primary cavity (W)
3000

Convection Element Wattages primary cavity (W)
2100

Microwave Wattages (W)
Drawer wattage (W)

Consumption and connection features

UPC code
825225802884

Product color
Stainless steel

Alternative colors available

Energy source
Electric

Watts (W)
4030

Current (A)
17

Volts (V)
208/220-240

Frequency (Hz)
60

Approval certificates
ETL

Power Cord Length
39 3/8

Plug type
fixed connection

Required cutout size (HxWxD) (in)
23 1/4 " x 22 1/16 " x 21 11/16 "

Product packaging dimensions (HxWxD) (in)
30.70 x 26.77 x 29.92

Net weight (lbs)
125

Gross weight (lbs)
133

2013-10-19
Page 1

The electrical outlet needs to be planned outside the cut-out niche.

Rating

Total rating 4.0 kW.
Total Amps: 17 A.
208 / 220 - 240 V / 60 Hz
Connecting cable 39 3/8 without plug (hardwire required).

BO451610
400 series single oven
Stainless steel-backed full glass door
Width 24" (60 cm)
Left-hinged
controls on top

2013-10-19
Page 2

