



Color Variants

VF411610
Stainless steel
Width 15 "

Included accessories

1 x deep-fat frying basket.
1 x Stainless steel appliance cover.

Optional accessories

FK020000
Additional frying basket
VZ400700
Vario timer connecting strip 400 series

VF411610

Vario electric deep fryer 400 series

Stainless steel

Width 15 "

- Three-zone frying basin: Foaming expansion rim, Frying zone, cold oil zone with residue strainer. No flavor transfer.
- Exact temperature setting, no drop in output
- Integrated frying basket suspension.

Features

Two control knobs with illuminated ring, temperature marking and oil/fat selection.

Electronic temperature control between 275 °F and 380 °F, in 10 °F increments.

Gentle fat melting stage

Three-zone basin

Cold oil zone

Foaming edge

Oil Quantity: 3.7 quarts (3.5 liters)

Oil drain valve with child lock

Safety lock.

Swing-out heating element (3,000 W)

Cleaning stage

Planning notes

Built-in control box is fitted in base cabinet at drawer level.

Front panel thickness 5/8" - 1".

The details below must be observed if the panel is more than 1" thick (there must be a recess at the rear for proper control module installation).

Plan a door in the base cabinet for operation of the oil drain-valve.

A minimum clearance of at least 1 9/16" from the appliance edge to the wall or to adjacent cabinets must be observed.

Clamping range: 1 13/16" - 2".

VF 411 and VK 411 must not be installed directly next to each other. Plan for a connecting cable.

Product Features

Product name / series name

Vario/Domino deep fryer

Construction type

Built-in

Energy source

Electric

Oven Control

electrical

Type of control

Sword knobs

Required cutout size (HxWxD) (mm)

270 x 360 x 490

Width of the product (mm)

380

Overall appliance dimensions (HxWxD)

(mm)

278.0 x 380 x 510

Net weight (kg)

14.000

Gross weight (kg)

15.000

Power on indicator

Yes

Location of control panel

Hob front

Type of regulation

Stepless energy regulated

Basic surface material

Stainless steel

Color of surface

Stainless steel, Stainless steel

Color of frame

Stainless steel

Approval certificates

CE, VDE

Power cord length (cm)

Consumption and connection features

Watts (W)

3000

Current (A)

13; 16

Volts (V)

220-240

Frequency (Hz)

50; 60

2013-04-22

Page 1