



Color Variants

VK411610
Stainless steel
Width 12"

Included accessories

2 x cooking insert.
1 x glass cover.
1 x hand grip.
1 x residuary filter.
1 x water drain valve.

Optional accessories

FK023000
Pasta basket.
GE020010
Unperforated cooking insert
GE020020
Perforated cooking insert
VD400000
Stainless steel cover
VZ400700
Vario timer connecting strip 400 series

VK411610

Vario in-counter steamer 400 series

Stainless steel

Width 12"

- Steaming in cooktop size
- Electronic water temperature control from 100 °F to 200 °F, in 5 °F increments.
- Cooking on two levels, without flavor transfer

Features

Two control knobs with illuminated ring, temperature marking and water drain.
Electronic water temperature control from 100 °F to 200 °F, in 10° increments.
Steam cooking level with electronic steam control for pressureless cooking.
Automatic boiling point detection.
Water capacity 1 - 6.4 quarts (1 - 6 liters).
Motor-driven 1/2" water drain valve
Safety lock.

Planning notes

Built-in control panel can be integrated in the bottom cabinet at drawer level.
Front panel thickness 5/8" - 1".
The details below must be observed if the panel is more than 1" thick (there must be a recess at the rear for proper control module installation).
The minimum distance from the appliance edge to the wall or furnishing components must be at least 2".
A ventilation hood must be installed when an upper cabinet is installed above the electric in-counter steamer.
If a cover is fitted, the glass lid must be removed when closing it.
Clamping range: 1 13/16" - 2".
Seal the worktop cutout.
VK 411 and VF 411 must not be installed directly next to one another.

Rating

Total rating: 1.8 kW
Plan for a connecting cable.

Product Features

Product name / series name
Vario/Domino steam cooker

Construction type
CONSTR_TYPE.Built-in

Energy source
Electric

Total number of cooktop burners

Type of control

Required cutout size (HxWxD) (mm)
280 x 360 x 490

Width of the product (mm)
380

Overall appliance dimensions (HxWxD) (mm)
288.0 x 380 x 510

Net weight (kg)
14.000

Gross weight (kg)
15.000

Residual heat indicator

Location of control panel

Basic surface material

Color of surface
Stainless steel, Stainless steel

Color of frame
Stainless steel

Approval certificates
ETL, ETL C

Power cord length (cm)

Consumption and connection features

Watts (W)
2300

Gas connection rating (W)

Current (A)
16; 10

Volts (V)
220-240

Frequency (Hz)
50; 60

2013-04-22
Page 1