



#### Color Variants

VP421610  
Stainless steel  
Width 12"

#### Included accessories

2 x spatula.

#### Optional accessories

VD400000  
Stainless steel cover  
VZ400700  
Vario timer connecting strip 400 series

VP421610

Vario teppan yaki 400 series

Stainless steel

Width 12"

- Hard chrome-plated surface for teppan cooking and use as a griddle, broiler, roast, and warming plate. No Pots or pans necessary.
- Electronic temperature control from 240°F to 480°F.
- Warming stage.

#### Features

Two control knobs with illuminated ring, cooking position and output marking. Electronic temperature control from 240°F to 480°F.

Two 1,500 W independently switchable grill zones each Warming stage.

Cooking area: W 12 3/16" x D 17 5/16". Safety lock.

Even with traces of use, always easy to clean like a cast pan

#### Planning notes

Front panel thickness 5/8" - 1".

The details below must be observed if the panel is more than 1" thick (there must be a recess at the rear for proper control module installation).

Above countertop minimum clearance of 21" from adjacent heat-sensitive cabinets or contact surfaces must be observed or thermal insulation must be installed.

The distance from the upper edge of the counter top to the upper edge of the intermediate shelf must be at least 4".

Intermediate shelf required; after installation this shelf must only be removed from below by using tools that guarantee touch protection.

Clamping range: 1 13/16" - 2".

Plan for a connecting cable.

#### Rating

Total rating: 1.8 kW

#### Product Features

Product name / series name

Vario/Domino Teppan Yaki

Construction type

Built-in

Energy source

Electric

Oven Control

electrical

Grill grating material

Required cutout size (HxWxD) (mm)

90 x 360 x 490

Width of the product (mm)

380

Overall appliance dimensions (HxWxD) (mm)

98.0 x 380 x 510

Net weight (kg)

16.000

Gross weight (kg)

17.000

Residual heat indicator

Location of control panel

Hob front

Basic surface material

Stainless steel

Color of surface

Stainless steel, Stainless steel

Color of frame

Stainless steel

Approval certificates

ETL, ETL C

Power cord length (cm)

140.0

#### Consumption and connection features

Watts (W)

Gas connection rating (W)

Current (A)

10

Volts (V)

208/220-240

Frequency (Hz)

60

2013-04-22

Page 1