FRIGIDAIRE

Home Comfort



FFHP223WS2 Indoor



FFHP223CS2 Outdoor

Signature Features

Quick Cool & Quick Warm

When you need to cool down quickly or warm up faster, use the quick cool/warm mode to speed up the fan.

Programmable 24-Hour On/Off Timer

Customize times to fit your schedule for immediate comfort when you get home. The built-in timer allows you to preset the unit to turn on and off in half-hour increments.

Effortless[™] Temperature Control

Our air conditioners maintain the preset room temperature, so you will remain comfortable at all times.

Sleep Mode

Maximum comfort throughout the evening hours with the added benefit of energy savings. With Sleep Mode, the temperature gradually increases a few degrees over the evening.

Ductless Mini-Split Air Conditioner/Heat Pump

Product Dimensi Evaporator (Indo		
Height	12-13/16"	
Width	42-1/2"	
Depth	9-3/4"	
Product Dimensi Condenser (Outo	••	
	••	
Condenser (Outo	door) Model	
Condenser (Outo	31-1/8"	

More Easy-To-Use Features

Multi-Speed Fan

Features three different fan speeds, for more cooling flexibility.

Effortless[™] Restart

Automatically resumes operating at its previous settings when power is restored to your unit.

Effortless™ Clean Filter

Our antibacterial filter reduces bacteria, room odors and other airborne particles for a healthier, more comfortable environment.

Ready-Select[®] Controls

Easily select options with the touch of a button.

Electronic Controls

Allow you to set the comfort level to your preference, while a convenient temperature readout displays the set temperature.



ENERGY STAR*

ENERGY STAF

Performance	BTUs
Cool	22,000
Heat	23,000

FRIGIDAIRE

Home Comfort

С

FFHP223SS2 Ductless Mini-Split Air Conditioner/Heat Pump

1odel Numbers	
Set Model Number	FFHP223SS2
ndoor Unit Part Number	FFHP223WS2
Outdoor Unit Part Number ¹	FFHP223CS2
Performance	
3TU (Cool)	22,000
BTU (Heat Pump)	23,000
Cooling Area (Sq. Ft.)	1,300
SEER (Air Conditioner)	20.0
HSPF (Heat Pump)	10.0
nverter Technology	Yes
COP	3.30
Electrical	
Volts	230V/208V
Min Circuit Ampacity	20 A
Maximum Circuit Breaker	30 A
Rated Watts (Cool)	1,760
Rated Watts (Heat)	2,000
Features	
Controls	Ready-Select [®] Controls
Fan Speeds (Cool/Fan/Heat)	4/3/4
ow Voltage Start-Up	Yes
Turbo Fan	Yes
Auto Fan	Yes
Energy Saver	
Lifergy Suver	
Sleep Mode	Yes
	Yes Yes
Sleep Mode	
Sleep Mode 24-Hour On/Off Timer	Yes
Sleep Mode 24-Hour On/Off Timer Remote Control	Yes Full-Function
Sleep Mode 24-Hour On/Off Timer Remote Control Air CFM (High/Med/Low) Indoor	Yes Full-Function 706/647/588/530
Sleep Mode 24-Hour On/Off Timer Remote Control Air CFM (High/Med/Low) Indoor Air Direction Control (Vert./Horz.)	Yes Full-Function 706/647/588/530 Swing/Manual
Sleep Mode 24-Hour On/Off Timer Remote Control Air CFM (High/Med/Low) Indoor Air Direction Control (Vert./Horz.) Air Discharge (Full-Width)	Yes Full-Function 706/647/588/530 Swing/Manual Bottom
Sleep Mode 24-Hour On/Off Timer Remote Control Air CFM (High/Med/Low) Indoor Air Direction Control (Vert./Horz.) Air Discharge (Full-Width) Filter Type	Yes Full-Function 706/647/588/530 Swing/Manual Bottom Antimicrobial Mesh
Sleep Mode 24-Hour On/Off Timer Remote Control Air CFM (High/Med/Low) Indoor Air Direction Control (Vert./Horz.) Air Discharge (Full-Width) Filter Type Filter Access	Yes Full-Function 706/647/588/530 Swing/Manual Bottom Antimicrobial Mesh Slide-Out
Sleep Mode 24-Hour On/Off Timer Remote Control Air CFM (High/Med/Low) Indoor Air Discharge (Full-Width) Filter Type Filter Access dB Indoor (Turbo)(High/Med/Low)	Yes Full-Function 706/647/588/530 Swing/Manual Bottom Antimicrobial Mesh Slide-Out (48)44/40/36
Sleep Mode 24-Hour On/Off Timer Remote Control Air CFM (High/Med/Low) Indoor Air Discharge (Full-Width) Filter Type Filter Access dB Indoor (Turbo)(High/Med/Low) dB Outdoor	Yes Full-Function 706/647/588/530 Swing/Manual Bottom Antimicrobial Mesh Slide-Out (48)44/40/36 59
Sleep Mode 24-Hour On/Off Timer Remote Control Air CFM (High/Med/Low) Indoor Air Direction Control (Vert./Horz.) Air Discharge (Full-Width) Filter Type Filter Access dB Indoor (Turbo)(High/Med/Low) dB Outdoor Warranty ²	Yes Full-Function 706/647/588/530 Swing/Manual Bottom Antimicrobial Mesh Slide-Out (48)44/40/36 59
Sleep Mode 24-Hour On/Off Timer Remote Control Air CFM (High/Med/Low) Indoor Air Direction Control (Vert./Horz.) Air Discharge (Full-Width) Filter Type Filter Access dB Indoor (Turbo)(High/Med/Low) dB Outdoor Warranty ² Included Accessories	Yes Full-Function 706/647/588/530 Swing/Manual Bottom Antimicrobial Mesh Slide-Out (48)44/40/36 59 Yes
Sleep Mode 24-Hour On/Off Timer Remote Control Air CFM (High/Med/Low) Indoor Air Direction Control (Vert./Horz.) Air Discharge (Full-Width) Filter Type Filter Access dB Indoor (Turbo)(High/Med/Low) dB Outdoor Warranty ² Included Accessories Drain Kit (Outdoor Unit)	Yes Full-Function 706/647/588/530 Swing/Manual Bottom Antimicrobial Mesh Slide-Out (48)44/40/36 59 Yes Yes Yes

¹Includes 25 ft. line set ²5 year parts only

NOTE: For planning purposes only. Always consult local and national electric codes. Refer to Product Installation Guide for detailed installation instructions on the web at frigidaire.com.

Product Dimensions	
Indoor –	
A-Height	12-13/16"
B-Width	42-1/2"
C-Depth	9-3/4"
Outdoor -	
A-Height	31-1/8″
B-Width	38-5/8″
C-Depth	16-13/16"

¹Illustration may not represent actual model.

All refrigeration and electrical work must be performed by a certified and licensed refrigeration technician for parts warranty validation. Insulated line sets and control wires are required and available for Frigidaire split systems in 25 ft. length. Each line set is equipped with flare nuts on both ends. Each system requires one line set for each indoor unit installed.

Accessories information available on the web at **frigidaire.com**

FRIGIDAIRE

USA • 10200 David Taylor Drive • Charlotte, NC 28262 • 1-800-FRIGIDAIRE • frigidaire.com CANADA • 5855 Terry Fox Way • Mississauga, ON L5V 3E4 • 1-800-265-8352 • frigidaire.ca FFHP223SS2 03/16 © 2016 Electrolux Home Products, Inc.

Ductless Mini-Split System Air Conditioner/Heat Pump **Submittal Sheet**


FRIGIDAIRE

FFHP223SS2

Job:	Reference:	Construction:
Location:	Approval:	Unit Number:
Engineer:	Date:	Drawing Number:
Submitted to:	_ Submitted by:	

Power	
Min Circuit Ampacity	20 A
Maximum Circuit Breaker	30 A
Capacities	
Cooling	22,000 BTU
Cooling Watts	1,760 W
Min/Max Cooling	6,800 Btu/27,300 Btu
Heatpump Capacity (BTU)	23,000 BTU
HSPF	10.0
Outdoor Sound Rating	59 dB (A)
SEER	20.0
EER	12.5
Low Ambient Cooling	0 – 115°F
Low Ambient Heating	-5 - 75°F
Voltage/Frequency	230V/208V/60Hz
Dehumidification	4.2 PT/H

Indoor Unit	FFHP223WS2
Dimensions (H x W x D)	12-13/16" x 42-1/2" x 9-3/4"
Max. Wall Thickness	18″
Sound Rating	(48) 44/40/36
Net Weight	36 lb
Shipping Weight	43 lb
Fan Motor Load	.38 A
Number of Fan Speeds	4
Fan Type	Cross flow
RPM at High Speed (cool)	1,300 RPM
Coil Type	aluminum fin & copper tube
Fin Type	coated fin
Ріре Туре	copper internal thread
Fin Rows (FPI)	2
Tube Diameter	7mm (5/16")
Drain Connection Size	16mm (5/8")
Compressor	
Compressor Type	Twin Rotary
Compressory Control	DC Inverter
Compressor Load	14.67 A
Locked Rotor Amps	25 A




FFHP223WS21 Indoor

¹Illustration may not represent actual model.

FRIGID∆IRE

USA • 10200 David Taylor Drive • Charlotte, NC 28262 • 1-800-FRIGIDAIRE • frigidaire.com CANADA • 5855 Terry Fox Way • Mississauga, ON L5V 3E4 • 1-800-265-8352 • frigidaire.ca FFHP223SS2 03/16

Outdoor Unit	FFHP223CS2
Dimensions (H x W x D)	31-1/8" x 38-5/8" x 16-13/16"
Sound Rating	59 dB (A)
Net Weight	153 lb
Shipping Weight	164 lb
Fan Motor Load	.65 A
Drive Type	inverter
CFM (high)	2,353
Fan Type	axial flow
Number of Speeds	DC
RPM	820
Coil Type	aluminum fin & copper tube
Fin Type	coated fin
Ріре Туре	copper internal thread
Fin Rows (FPI)	2
Tube Size	7 mm (5/16")
Features	
Controls	mircoprocessor
Remote Control	lcd wireless
Temperature Control	61-86°F (16-30°C)
Timer	24 hr
Air Louvers	2 pieces
Horizontal	manual
Vertical	swing
Low Voltage Restart	built-in
Self-Diagnosis	yes
Air Filter	washable, anti-mold
Refrigerant System	
Refrigerant	R410A
Ounces	77.6
Lineset	25 ft
Maximum Height	33 ft
Maximum Line Length	82 ft
Discharge Vapor Line (od)	6 mm (1/4")
Suction (od)	16 mm (5/8")
Operating Range	
Indoor Air Cooling Intake Temp Range	>= 61°F
Indoor Air Heating Intake Temp Range	<= 86°F
Outdoor Air Cooling Intake Temp Range	0~115°F
Outdoor Air Heating Intake Temp Range	-5~75°F



FFHP223CS21 Outdoor

