

PRODUCT INDEX



elica

aria nuova

**Register your product at elica.com
and get 1 extra year of warranty.**


3 YEARS

PARTS AND LABOR FULL WARRANTY

2+1 extra year when you register your product at elica.com
Applies for all Elica products. For U.S & Canada users only.
For valid warranty extension, register within 3 months from purchase.



—| ELICA INDEX V. 2022

				
Model Name	Asti 22" Comfort Series	Asti 28" Comfort Series	Asti 30" Comfort Series	
Model Numbers	EAS422SS	EAS428S2	EAS430SS	
Dimensions	22 1/2" W x 10 3/4" D x 9 1/2" H	28 1/4" W x 10 3/4" D x 9 1/2" H	30" W x 12" D x 9 1/8" H	
Blower Type	400 CFM(3-speed)	400 CFM(3-speed)	400 CFM(3-speed)	
CFM Reduction	Yes with/ KIT0175561	Yes	Yes with/ KIT0175561	
Noise (sones)	5.9 Sones	5.9 Sones	5.9 Sones	
Finish	Stainless Steel	Stainless Steel	Stainless Steel	
Controls	Backlit Electronic Push Button	Stainless Steel look, backlit touch control	Mechanical Push Button	
Illumination	2 LED, 2.1 W 4000 K	2 LED, 2.1 W 3000 K	2 LED , 6.5 W, 3000 K	
Filter Type	Dishwasher-Safe, Anodized Aluminum Mesh	Dishwasher-Safe, Anodized Aluminum Mesh	Aluminum Mesh + Stainless Steel Layer	
Duct Transition	6" Round with BackDraft Damper (top only)	6" Round with BackDraft Damper (top only)	6" Round with BackDraft Damper (top only)	
Installation Type	Ducted or Recirculating w/kit	Ducted or Recirculating w/kit	Ducted or Recirculating w/kit	
Electrical	120 V - 60 Hz, 289 W	120 V - 60 Hz, 289 W	120 V - 60 Hz, 260 W	
Kits Available	KIT0175561 (CFM Reduction) KIT02770 (Recirculating Kit)	KIT02773 (30" liner) KIT02774 (36" liner) KIT02770 (Recirculating Kit)	KIT0175561 (CFM Reduction) KIT02773 (30" liner) KIT02770 (Recirculating Kit)	

				
Model Name	Palermo Techne Series	Trento Elica Pro Series	Arezzo Elica Pro Series	
Model Numbers	EPR628S1 EPR634SS	ETR634SS (600 CFM) ETR134S1 (1200 CFM) ETR146SS (1200 CFM)	EAR628S4 EAR634SS EAR134S4 EAR140S4 EAR146S4	
Dimensions	28 1/4"W x 10 3/4"D x 9 1/2"H 34 1/5"W x 10 3/4"D x 9 1/2"H	34 1/2"W x 18"D x 11 1/2"H 46 1/2"W x 18"D x 11 1/2"H	28 1/2"W x 22"D x 11 1/2"H 34 1/2"W x 22"D x 11 1/2"H 40 1/2"W x 22"D x 11 1/2"H 46 1/2"W x 22"D x 11 1/2"H	
Blower Type	600 CFM(3-speed)	34" 600 CFM (4-speed) 34"46" 1200 CFM (4-speed)	28", 34" 600 CFM(4-speed) - 34", 40" & 46" 1200 CFM(4-speed) -	
CFM Reduction	Yes with/ KIT02748	No	No	
Noise (sones)	6.8 Sones	7 Sones (34") 8.5 Sones (34",46")	Sones 7 (28",34") Sones 8.5 (34",40",46")	
Finish	Stainless Steel	Stainless Steel	Stainless Steel	
Controls	Stainless Steel Push Button	Fully Retractable Rotating Knobs w/ Blue Backlighting	Fully Retractable Rotating Knobs w/ Blue Backlighting	
Illumination	2 Premium LED, 2.5 W, 4000K	2 LED, 6.5 W, 3000K *Consumer Replaceable	2 LED, 7.5 W, 3000K (28",34") 4 LED, 7.5 W, 3000K (40",46") *Consumer Replaceable	
Filter Type	2 Dishwasher-Safe, Stainless Steel Baffle Slot Grease Filter	Dishwasher-Safe, Professional Stainless Steel Angled Baffle Filter	Dishwasher-Safe, Professional Stainless Steel Angled Baffle Filter	
Duct Transition	6" Round with BackDraft Damper (top only)	10" Round with BackDraft Damper (top only)	10" Round with Back Draft Damper (Top only)	
Installation Type	Ducted or Recirculating with kit	Ducted Installation Only	Ducted Installation Only	
Electrical	120 V - 60 Hz, 445 W	120 V - 60 Hz, 490 W 120 V - 60 Hz, 926 W	120 V - 60 Hz, 463 W (28") 120 V - 60 Hz, 490 W (34") 120 V - 60 Hz, 913 W (34") 120 V - 60 Hz, 926 W (46")	
Kits Available	KIT02773 (30" liner) KIT02774 (36" liner) KIT02770 (Recirculating Kit) KIT02748 (CFM Reduction Kit)	KIT0153054 (External blower) KIT0154387 (In-line blower)	KIT0153054 (External blower) KIT0154387 (In-line blower)	

SPECS

Undercabinet

NEW

				
Model Name	Fusaro Comfort Series	Nemi Comfort Series	Gubbio Comfort Series	
Model Numbers	EFS130SS	ENM230S1 ENM236S1 ENM230W1 ENM230B1	EGB224SS	
Dimensions	30"W x 18 5/8"D x 5"H	30"W x 18 5/8"D x 5"H 36"W x 18 5/8"D x 5"H	24"W x 18 7/8"D x 5"H	
Blower Type	190 CFM(2-speed)	280 CFM(3-speed)	250 CFM(3-speed)	
CFM Reduction	No	No	No	
Noise (sones)	4.1 Sones	4.9 Sones	4.6 Sones	
Finish	Stainless Steel	Stainless Steel, Black & White	Stainless Steel	
Controls	Rocker Switches	Backlit Electronic Push Button	Mechanical Slider Control	
Illumination	1.75w Incandescent lamp (Not included)	2 LED, 2.1 W, 4000 K	2 LED, 2.1 W 3000 K	
Filter Type	Dishwasher-Safe, Anodized Aluminum Mesh	Dishwasher-Safe, Anodized Aluminum Mesh	2 Dishwasher-Safe, Anodized Aluminum Mesh	
Duct Transition	3 1/4" x 10" (Top or Rear) or 7" Round (sold separately)	3 1/4" x 10" (Top or Rear) or 7" Round (sold separately)	3 1/4" x 10" with Back Draft Damper (Top or Rear)	
Installation Type	Ducted or Recirculating with kit	Ducted or Recirculating with kit	Ducted or Recirculating with kit	
Electrical	120 V - 60 Hz, 110 W	120 V - 60 Hz, 115 W	120 V - 60 Hz, 115 W	
Kits Available	KIT02722 (7" duct transition) KIT02723 (7" Back Draft) KIT02724 (No return valve)	KIT02722 (7" duct transition) KIT02723 (No return valve) KIT0140997 (Recirculating kit)	KIT02722 (7" duct transition) KIT02723 (No return valve) KIT0140997 (Recirculating kit)	

SPECS

Undercabinet

				
Model Name	Allasio Comfort Series	TT Comfort Series		
Model Numbers	EAL330S2 EAL336S2 EAL330S2* EAL336S2*	ETT424S1 ETT430SS ETT436SS		
Dimensions	30"W x 20"D x 4 7/10"H 36"W x 20"D x 4 7/10"H 30"W x 20"D x 4 1/2" H*	24"W x 11-17"D x 11 3/4"H 30"W x 11-17"D x 11 3/4"H 36"W x 11-17"D x 11 3/4"H		
Blower Type	300 CFM(3-speed)	400 CFM(3-speed)		
CFM Reduction	Yes	Yes		
Noise (sones)	5.2 Sones	5.9 Sones		
Finish	Stainless Steel	Stainless Steel		
Controls	Electronic Touch Controls with Adjustable Color Backlight Backlit Electronic Push Button*	Hidden Electronic Touch Controls with LCD		
Illumination	2 LED, 2.1 W, 3000 K	2 LED , 2.1 W 3000K		
Filter Type	2 Dishwasher-Safe, Anodized Aluminium Mesh	Dishwasher-Safe, Anodized Aluminum Mesh Filter		
Duct Transition	3 1/4" x 10" with Back Draft Damper (Top or Rear)	6" Round Top Discharge		
Installation Type	Ducted or Recirculating with kit	Ducted or Recirculating with kit		
Electrical	120 V - 60 Hz, 360 W 120 V - 60 Hz, 273 W*	120 V - 60 Hz, 245 W		
Kits Available	KIT02723 (No return valve) KIT02178 - KIT02179 (Recirculating Kit) GRI0131086A - GRI0131087A (Upgrade Filter Kit) KIT 02591 (Grease filter replacement)*	CFC0038668 (Charcoal Filter kit) KIT02748 (CFM Reduction Kit)		

SPECS

Undercabinet

				
Model Name	Bellagio Techne Series	Aria Techne Series	Modena Techne Series	
Model Numbers	EBL430S1 EBL436S1	EAI430SS EAI436SS	EMD530S3 EMD536S3	
Dimensions	30"W x 20"D x 4 1/2"H 36"W x 20"D x 4 1/2"H	30"W x 20"D x 4 7/10"H 36"W x 20"D x 4 7/10"H	30"W x 19 5/8"D x 9 3/4"H 36"W x 19 5/8"D x 9 3/4"H	
Blower Type	400 CFM (3-speed + boost)	430 CFM (3-speed + boost)	600 CFM (3-speed + boost)	
CFM Reduction	Yes	Yes	Yes	
Noise (sones)	6.1 Sones	6.1 Sones	6.8 Sones	
Finish	Stainless Steel	Stainless Steel + Black Glass	Stainless Steel + Black Glass	
Controls	Multi-function Electronic with LCD Display	Capacitive Touch (Glass)	Capacitive Touch (Glass)	
Illumination	2 LED, 6.5 W, 3000 K	2 Premium LED Dimmable, 2.5 W, 4000 K	2 Premium LED Dimmable, 2.5 W, 4000 K	
Filter Type	2 Dishwasher-Safe, Anodized Aluminum Mesh Grease Filter	2 Dishwasher-Safe, Stainless Steel Baffle Slot Filter	Dishwasher-Safe, Stainless Steel Microhole Grease Filter	
Duct Transition	3 1/4" x 10" (Top or Rear) or 7" Round (sold separately)	3 1/4" x 10" (Top or Rear) or 7" Round (sold separately)	3 1/4" x 10" (Rear outlet) or 6" Round (Top outlet)	
Installation Type	Ducted or Recirculating with kit	Ducted or Recirculating with kit	Ducted or Recirculating with kit	
Electrical	120 V - 60 Hz, 445 W	120 V - 60 Hz, 333 W	120 V - 60 Hz, 445 W	
Kits Available	KIT02723 (No return valve) KIT02178 - KIT02179 (Recirculating Kit)	KIT02723 (7" Back Draft) KIT02178 - KIT02179 (Recirculating Kit)	KIT02667 (Recirculating Kit)	

SPECS

Undercabinet - Wall Mount Hoods

				
Model Name	Sora Comfort Series	Cervinia Elica Pro Series	Calabria Elica Pro Series	
Model Numbers	ESR430S1 ESR436S1	ECV630S3 ECV636S3	ECL630S4 ECL136S4 ECL636SS ECL142S4 ECL148S4	
Dimensions	30"W x 23"D x 10"H 36"W x 23"D x 10"H	30"W x 23"D x 11 1/32"H 36"W x 23"D x 11 1/32"H	30"W x 25"D x 18"H 36"W x 25"D x 18"H 42"W x 25"D x 18"H 48"W x 25"D x 18"H	
Blower Type	400 CFM(2-speed)	600 CFM(4-speed)	30",36" 600 CFM(4-speed) 36",42",48" 1200 CFM (4-speed)	
CFM Reduction	Yes	No	No	
Noise (sones)	5.9 Sones	7 Sones	Sones 7 (30",36") Sones 8.5 (36",42",48")	
Finish	Stainless Steel	Stainless Steel	Stainless Steel	
Controls	Rocker Switches	Fully Retractable Rotating Knobs w/ Blue Backlighting	Fully Retractable Rotating Knobs w/ Blue Backlighting	
Illumination	2 LED, 2.1 W 4000 K	2 LED, 6.5 W, 3000K *Consumer Replaceable	2 LED, 6.5 W, 3000K(30",36",42") 4 LED, 6.5 W, 3000K(48") *Consumer Replaceable	
Filter Type	Dishwasher-Safe, Stainless Steel Baffle Slot Grease Filter	2 Dishwasher-Safe, Professional Stainless Steel Angled Baffle Filter	Dishwasher-Safe, Professional Stainless Steel Angled Baffle Filter 2 (30", 36", 42") / 3(48")	
Duct Transition	3 1/4" x 10" with Back Draft Damper (Top or Rear)	3 1/4" x 10" with Back Draft Damper (Top or rear)	10" Round with Back Draft Damper (Top and Rear)	
Installation Type	Ducted or Recirculating with kit	Ducted Installation Only	Ducted Installation Only	
Electrical	120 V - 60 Hz, 265 W	120 V - 60 Hz, 457 W	120 V - 60 Hz, 463 W 120 V - 60 Hz, 490 W 120 V - 60 Hz, 913 W 120 V - 60 Hz, 926 W	
Kits Available	KIT02770 (Recirculating kit) KIT0175561 (CFM reduction)	KIT02159-KIT02158 (Chimney extension 6") KIT02160-KIT02161 (Chimney extension 12") KIT0142864 - KIT0142867 (Back Splash Kit)	KIT02159-KIT02158-KIT2622-KIT2164 (Chimney extension 6") KIT02160-KIT02161-KIT2623-KIT2165 (Chimney extension 12") KIT0153054 (External blower) KIT0154387 (In-line blower)	

SPECS

Chimney Hoods

				
Model Name	Volterra 24" Comfort Series	Volterra 30" 36" Comfort Series	Varna Techne Series	Varna Black Techne Series
Model Numbers	EVL424SS	EVL430S3 EVL436S3	EVR630S2 EVR636S2	EVR630BL EVR636BL
Dimensions	23 5/8"W x 19 5/8"D x 28 3/8" - 42 1/8"H	30"W x 19 5/8"D x 28 3/8" - 42 1/8"H 36"W x 19 5/8"D x 28 3/8" - 42 1/8"H	30"W x 19 11/16"D x 28 3/8" - 42 1/8"H 36"W x 19 11/16"D x 28 3/8" - 42 1/8"H	30"W x 19 11/16"D x 28 3/8" - 42 1/8"H 36"W x 19 11/16"D x 28 3/8" - 42 1/8"H
Blower Type	400 CFM(3-speed)	400 CFM(3-speed)	600 CFM (3-speed + boost)	600 CFM (3-speed + boost)
CFM Reduction	Yes/ KIT0175561	Yes	Yes	Yes
Noise (sones)	5.9 Sones	5.9 Sones	6.8 Sones	6.8 Sones
Finish	Stainless Steel	Stainless Steel	Stainless Steel + Black Glass	Black Stainless Steel + Black Glass
Controls	Backlit Electronic Push Button	Stainless steel look, backlit touch control	Capacitive touch (Glass)	Capacitive touch (Glass)
Illumination	2 LED, 2,1 W 4000 K	2 LED , 2,1 W 3000 K	2 Premium Dimmable LED 2.1 W, 4000 K	2 Premium Dimmable LED 2.1 W, 4000 K
Filter Type	2 Dishwasher-Safe, Anodized Aluminum Mesh	Dishwasher-Safe, Anodized Aluminum Mesh (2w/ 30" & 3w/36")	Dishwasher-Safe, Stainless Steel Microhole Grease Filter	Dishwasher-Safe, Stainless Steel Microhole Grease Filter
Duct Transition	6" Round with Back Draft Damper (Top only)	6" Round with Back Draft Damper (Top only)	6" Round with Back Draft Damper (Top Only)	6" Round Top Discharge (Top Only)
Duct Cover Dimension	8 3/16"	8 3/16"	8 3/16"	8 3/16"
Installation Type	Ducted or Recirculating with kit	Ducted or Recirculating with kit	Ducted or Recirculating with kit	Ducted or Recirculating with kit
Electrical	120 V - 60 Hz, 265 W	120 V - 60 Hz, 265 W	120 V - 60 Hz, 455 W	120 V - 60 Hz, 265 W
Kits Available	KIT02762 (Long Chimney) KIT0175561 (CFM reduction) KIT02766 (Recirculating Kit)	KIT02762 (Long Chimney) KIT02766 (Recirculating Kit)	KIT02762 (Long Chimney) KIT02766 - KIT02721A (Recirculating Kit)	KIT0140928 (Long Chimney) KIT02766 - KIT02721A (Recirculating Kit)

SPECS

Chimney Hoods

				
Model Name	Pilato Techne Series	Foglia Techne Series	Lugano Techne Series	
Model Numbers	EPL630S2 EPL636S2	EFG630S1 EFG636S1	ELG630S3 ELG636S3	
Dimensions	30"W x 21 1/2"D x 28 3/8 - 42 1/16"H 36"W x 21 1/2"D x 28 3/8 - 42 1/16"H	30"W x 19 11/16"D x 28 3/8 - 42 1/8"H 36"W x 19 11/16"D x 28 3/8 - 42 1/8"H	30"W x 19 7/8"D x 23 6/10 - 42 1/4"H 36"W x 19 7/8"D x 23 6/10 - 42 1/4"H	
Blower Type	600 CFM (3-speed + boost)	600 CFM (3-speed + boost)	600 CFM (3-speed + boost)	
CFM Reduction	Yes	Yes	Yes	
Noise (sones)	6.8 Sones	6.8 Sones	6.8 Sones	
Finish	Stainless Steel	Stainless Steel + Black Panel	Stainless Steel + Black Glass	
Controls	Multi-function Electronic with LCD Display	Capacitive touch (Glass)	Capacitive touch (Glass)	
Illumination	2 LED, 6.5 W, 3000 K	2 Premium Dimmable LED 2.1 W, 4000 K	2 Premium Dimmable LED 2.1 W, 4000 K	
Filter Type	Dishwasher-Safe, Stainless Steel Microhole Grease Filter	Dishwasher-Safe, Stainless Steel Microhole Grease Filter	Aluminum Mesh Filter + Perimeter Aspiration (3w/ 30" & 4w/36")	
Duct Transition	6" Round with Back Draft Damper (Top Only)	6" Round with Back Draft Damper (Top Only)	6" Round with Back Draft Damper (Top Only)	
Duct Cover Dimension	8 1/8"	8 3/16"	13"	
Installation Type	Ducted or Recirculating with kit	Ducted or Recirculating with kit	Ducted or Recirculating with kit	
Electrical	120 V - 60 Hz, 450 W	120 V - 60 Hz, 455 W	120 V - 60 Hz, 450 W 120 V - 60 Hz, 495 W	
Kits Available	KIT02762 (Long Chimney) KIT02766 - KIT02721A (Recirculating Kit)	KIT02784 (Long Chimney) KIT02766 - KIT02721A (Recirculating Kit)	KIT02785-KIT01935 (Long Chimney) KIT0141918 (Charcoal filter) KIT0141925 (Recirculating Kit)	


SPECS

Chimney Hoods

				
Model Name	Stoney Techné Series	Leone Elica Pro Series		
Model Numbers	EST630SS EST636SS	ELN630S2 ELN148SS ELN636SS ELN136S2 ELN142S2		
Dimensions	30"W x 19 7/8"D x 24 1/2" - 42 1/4"H 36"W x 19 7/8"D x 24 1/2" - 42 1/4"H	30"W x 24"D x 30" - 47 5/8" H 36"W x 24"D x 30" - 47 5/8" H 42"W x 24"D x 30" - 47 5/8" H 48"W x 24"D x 30" - 47 5/8" H		
Blower Type	600 CFM (3-speed + boost)	30",36" 600CFM(4-speed) 36",42",48" 1200CFM(4-speed)		
CFM Reduction	Yes	No		
Noise (sones)	6.8 Sones	7 Sones (30",36") 8.5 Sones (36",42",48")		
Finish	Stainless Steel + Black Glass	Stainless Steel		
Controls	Capacitive touch (Glass)	Fully Retractable Rotating Knobs w/ Blue Backlighting		
Illumination	2 Premium Dimmable LED 2.5 W, 4000 K	2 LED, 7.5 W, 3000 K *Consumer Replaceable		
Filter Type	Aluminum Mesh Filter + Perimeter Aspiration (3w/ 30" & 4w/36")	Dishwasher-Safe, Professional Stainless Steel Angled Baffle Filters (2w/30",36" & 42", 3w/48")		
Duct Transition	Round 6" Top Discharge	8" Round with Back Draft Damper (Top Only)		
Duct Cover Dimension	13"	13 1/8"		
Installation Type	Ducted or Recirculating with kit	Ducted Installation Only		
Electrical	120 V - 60 Hz, 460 W	120 V - 60 Hz, 463 W 120 V - 60 Hz, 490 W 120 V - 60 Hz, 913 W		
Kits Available	KIT02785 - KIT01935 (Long Chimney) KIT0141925 (Recirculating Kit)	KIT02785 (Long Chimney) KIT0153054 (External Blower) KIT0154387 (In Line Blower)		

SPECS

T- Shaped Chimney Hoods

				
Model Name	Toblino 24" Comfort Series	Toblino 30" 36" Comfort Series	Mezzano Techné Series	Vavano Elica Pro Series
Model Numbers	ETB424SS	ETB430S2 ETB436S2	EMZ630S3 EMZ636S3	EVV636S1 EVV648S1
Dimensions	24"W x 19 5/8"D x 20 1/2" - 35"H	30"W x 19 5/8"D x 20 1/2"H 36"W x 19 5/8"D x 20 1/2"H	30"W x 19 11/16"D x 29 11/16"H 36"W x 19 11/16"D x 29 11/16"H	36"W x 24"D x 30"H 48"W x 24"D x 30"H
Blower Type	400 CFM(3-speed)	400 CFM(3-speed)	600 CFM (3-speed + boost)	600 CFM(4-speed)
CFM Reduction	Yes/ KIT0175561	Yes	Yes	No
Noise (sones)	Min: 0.5, Max: 7.0	Min: 0.5, Max: 7.0	Min: 2 Max: 7.5	Min: 2, Max: 8
Finish	Stainless Steel	Stainless Steel	Stainless Steel + Black Glass	Stainless Steel
Controls	Backlit Electronic Push Button	Stainless steel look, backlit touch control	Capacitive Touch (Glass)	Fully Retractable Rotating Knobs w/ Blue Backlighting
Illumination	2 LED , 2.1 W 4000 K	2 LED 2.1 W , 3000 K	2 Premium Dimmable LED 2.1 W, 4000 K	2 LED, 6.5 W, 3000K *Consumer Replaceable
Filter Type	2 Dishwasher-Safe, Anodized Aluminum Mesh	Dishwasher-Safe, Anodized Aluminum Mesh (2w/30" & 3w/36")	Dishwasher-Safe, Stainless Steel Microhole Grease Filter	Dishwasher-Safe, Professional Stainless Steel Angled Baffle Filters (2w/36", 3w/48")
Duct Transition	6" Round with Back Draft Damper (Top Only)	6" Round with Back Draft Damper (Top Only)	6" Round with Back Draft Damper (Top Only)	8" Round with Back Draft Damper (Top Only)
Duct Cover Dimension	13"	13"	13"	13 5/64"
Installation Type	Ducted or Recirculating with kit	Ducted or Recirculating with kit	Ducted or Recirculating with kit	Ducted Installation Only
Electrical	120 V - 60 Hz, 260 W	120 V - 60 Hz, 260 W	120 V - 60 Hz, 455 W	120 V - 60 Hz 490 W
Kits Available	KIT0175561 (CFM Reduction) KIT02875 (Recirculating Kit) KIT02785 (Long Chimney)	KIT02875 (Recirculating Kit) KIT02785 (Long Chimney)	KIT0102875(Recirculating Kit) KIT02785 (Long Chimney)	KIT0154387 (In-line blower) KIT0153054 (External blower) KIT0146881-KIT02785 (Long Chimney)

SPECS

Chimney Island Hoods

				
Model Name	Salice Techne Series	Stoney Island Techne Series	Leone Island Elica Pro Series	
Model Numbers	ESL636S3 ESL642S3	ESI636SS ESI642SS	ELI136S2 ELI142S2	
Dimensions	36"W x 27 4/5"D x 32 4/5" - 52 4/5"H 42"W x 27 4/5"D x 32 4/5" - 52 4/5"H	36"W x 27"D x 32 4/5" - 52 4/5"H 42"W x 27"D x 32 4/5" - 52 4/5"H	36"W x 27"D x 37 1/2" - 46 9/16"H 42"W x 27"D x 37 1/2" - 46 9/16"H	
Blower Type	600 CFM(3-speed+boost)	600 CFM(3-speed+boost)	1200 CFM(4-speed)	
CFM Reduction	Yes	Yes	No	
Noise (sones)	6.8 Sones	6.8 Sones	8.5 Sones	
Finish	Stainless Steel + Black Glass	Stainless Steel + Black Glass	Stainless Steel	
Controls	Capacitive Touch (Glass)	Capacitive Touch (Glass)	Fully Retractable Rotating Knobs w/ Blue Backlighting	
Illumination	4 Premium Dimmable LED Lights, 2.5 watts	4 Premium Dimmable LED Lights, 2.5 watts	4 LED, 6.5 W, 3000K *Consumer Replaceable	
Filter Type	Aluminum Mesh Filter + Perimeter Aspiration (4 for 36" & 5 for 42")	Dishwasher Safe, Aluminum Grease Filter, Perimeter Aspiration	2 Dishwasher-Safe, Professional Stainless Steel Angled Baffle Filter	
Duct Transition	6" Round with Back Draft Damper (Top Only)	6" Round with Back Draft Damper (Top Only)	8" Round with Back Draft Damper (Top Only)	
Duct Cover Dimension	13 2/5"	13 2/5"	13 1/8"	
Installation Type	Ducted or Recirculating with kit	Ducted or Recirculating with kit	Ducted Installation Only	
Electrical	120 V - 60 Hz, 540 W	120 V - 60 Hz, 460 W	120 V - 60 Hz, 926 W	
Kits Available	KIT0141924(Recirculating Kit) KIT0100317 (Long Chimney) KIT0141918 (Charcoal filter)	KIT0141924 (Recirculating Kit) KIT02721 (Long Chimney)	KIT0153054 (External blower) KIT0154387 (In-line blower) KIT02785 - KIT0100317 (Long Chimney)	

SPECS

T Shaped Island Hoods

				
Model Name	Maggiore Techne Series	Vavano Island Elica Pro Series		
Model Numbers	EMG636S1 EMG642S1	EVI642S1 EVI648S1		
Dimensions	36"W x 27 1/8"D x 29 13/16"- 50 1/8"H 42"W x 27 1/8"D x 29 13/16"- 50 1/8"H	42"W x 24"D x 30" - 51" H 48"W x 24"D x 30" - 51" H		
Blower Type	600 CFM(3-speed+boost)	600 CFM(4 Speed)		
CFM Reduction	Yes	No		
Noise (sones)	6.8 Sones	7 Sones		
Finish	Stainless Steel + Black Glass	Stainless Steel		
Controls	Capacitive Touch (Glass)	Fully Retractable Rotating Knobs w/ Blue Backlighting		
Illumination	4 Premium Dimmable LED 2.1 watts, 4000 K	4 LED, 6.5 W, 3000K *Consumer Replaceable		
Filter Type	3 Dishwasher-Safe, Stainless Steel Microhole Filter	3 Dishwasher-Safe, Professional Stainless Steel Angled Baffle Filters		
Duct Transition	6" Round with Back Draft Damper (Top only)	8" Round with Back Draft Damper (Top Only)		
Duct Cover Dimension	13"	13"		
Installation Type	Ducted or Recirculating with kit	Ducted Installation Only		
Electrical	120 V - 60 Hz, 426 W	120 V - 60 Hz, 480 W		
Kits Available	KIT02665(Recirculating Kit) KIT0100317 (Long Chimney) KIT02667 (Charcoal filter)	KIT0145610 (Long Chimney) KIT0154387 (In-line blower) KIT0153054(External blower)		


SPECS

Hanging Hoods

		 NEW		
Model Name	Easy Iconic Series	Seashell Iconic Series		
Model Numbers	EES320SS EES320WT	ESS432SS		
Dimensions	20 1/4" W x 20 1/4" D x 21" - 51" H	31 13/32" W x 22 13/32" - 61 13/32" H		
Blower Type	355 CFM (3-speed + booster)	400 CFM(4-speed)		
CFM Reduction	No	No		
Noise (sones)	6.8 Sones	5.9 Sones		
Finish	Stainless Steel / White	Mirror Stainless Steel		
Controls	Electronic Push with perimetral light	3S+B Remote Control		
Illumination	3 LED, 2.5 W, 4000 K	4 Strip LED + Led Disk, 3500 K		
Filter Type	Aluminum Mesh Filter + Perimeter Aspiration	Aluminium grease filter + Regenerable charcoal filter		
Duct Transition	Not applicable	Not applicable		
Installation Type	Recirculating Installation Only	Recirculating Installation Only		
Electrical	120 V - 60 Hz 460 W	120 V - 60 Hz		
Kits Available	KIT0121394 (Wallmounting Bracket) KIT01921 (High ceiling extension)	KIT0067590 (Ext. Cable) KIT0121469 (Black remote control) KIT0121468 (White remote control)		

SPECS

Curved Glass Hoods

				
Model Name	Potenza Comfort Series	Como Techne Series	Cingoli Techne Series	
Model Numbers	EPT430S3 EPT436S3	ECM630S3 ECM636S3	ECN636S3 ECN642S3	
Dimensions	30"W x 19 5/8"D x 20 3/8" - 36 5/8"H 36"W x 19 5/8"D x 20 3/8" - 36 5/8"H	30"W x 19 11/16"D x 29 11/16" - 54 1/6"H 36"W x 19 11/16"D x 29 11/16" - 54 1/6"H	36"W x 19 11/16"D x 29 13/32"H 42"W x 25 1/4"D x 29 13/32"H	
Blower Type	400 CFM (3-speed)	600 CFM (3-speed + boost)	600 CFM (3-speed + boost)	
CFM Reduction	Yes	Yes	Yes	
Noise (sones)	5.9 Sones	6.8 Sones	6.8 Sones	
Finish	Stainless Steel	Stainless Steel + Black Glass	Stainless Steel + Black Glass	
Controls	Stainless steel look, electronic touch control	Capacitive Touch (Glass)	Capacitive Touch (Glass)	
Illumination	2 LED, 2.1 W, 3000 K	2 Premium LED Dimmable 2.1 W, 4000 K	2 Premium Dimmable LED 2.1 W 4000 K	
Filter Type	Dishwasher-Safe, Anodized Aluminum Mesh Filter	Dishwasher-Safe, Stainless Steel Microhole Filter	Dishwasher-Safe, Stainless Steel Micro Hole Grease Filter	
Duct Transition	6" Round with Back Draft Damper (Top Only)	6" Round with Back Draft Damper (Top Only)	6" Round with Back Draft Damper (Top Only)	
Duct Cover Dimension	13"	13"	13"	
Installation Type	Ducted or Recirculating with kit	Ducted or Recirculating with kit	Ducted or Recirculating with kit	
Electrical	120 V - 60 Hz, 301 W	120 V - 60 Hz 395 W	120 V - 60 Hz, 394 W	
Kits Available	KIT0102875 (Recirculating Kit) KIT0100315 (Long Chimney)	KIT02667 (Charcoal filter) KIT0100315 (Long Chimney) KIT02721A - KIT02766 (Recirculating Kit)	KIT02665 (Recirculating Kit) KIT0100317 (Long Chimney) KIT02667 (Recirculating Kit)	

SPECS

Wall Mount and Island Hoods

				
Model Name	Haiku Wall 13" Iconic Series	Haiku Island 13" Iconic Series	Haiku Wall Iconic Series	Haiku Island Iconic Series
Model Numbers	EHK613SS	EHI613SS	EHK624SS EHK636SS EHK636BL EHK636WH EHK648SS	EHI648SS EHI648BL EHI648WH EHI670SS
Dimensions	13" W x 12 3/5" D x 32"- 49" H	13" W x 13" D x 33"- 49" H	24" W x 12 3/5" D x 32"- 49" H 36" W x 12 3/5" D x 32"- 49" H 36" W x 12 3/5" D x 32"- 49" H 36" W x 12 3/5" D x 32"- 49" H 48" W x 12 3/5" D x 32"- 49" H	48" W x 13" D x 33"- 49"H 48" W x 13" D x 33"- 49"H 48" W x 13" D x 33"- 49"H 70" W x 13" D x 33"- 49"H
Blower Type	600 CFM (3 speed + Boost)	600 CFM (3 speed + Boost)	600 CFM (3 speed + Boost)	600 CFM (3 speed + Boost)
CFM Reduction	No	No	No	No
Noise (sones)	7 Sones	7 sones	7 sones	7 sones
Finish	Stainless Steel	Stainless Steel	Stainless Steel /Clear Black Glass / White KRION®	Stainless Steel /Clear Black Glass / White KRION®
Controls	Sensitive Touch Control with backlight	Sensitive Touch Control with backlight	Sensitive Touch Control with backlight	Sensitive Touch Control with backlight
Illumination	Strip LED, 7 W, 3500 K	Strip LED 1 x 7 W 3500 K	Strip LED 1 x 7 W 3500 K	Strip LED 1 x 7 W 3500 K
Filter Type	Sophisticated black iron grates + 6 layer mesh filter	Sophisticated black iron grates + 6 layer mesh filter	Sophisticated black iron grates + 6 layer mesh filter	Sophisticated black iron grates + 6 layer mesh filter
Duct Transition	6" Round Top Discharge	6" Round Top Discharge	6" Round Top Discharge	6" Round Top Discharge
Duct Cover Dimension	12"	12"	12"	12"
Installation Type	Ducted or recirculating with kit	Ducted or recirculating with kit	Ducted or recirculating with kit	Ducted or recirculating with kit
Electrical	120 V - 60 Hz, 460 W	120 V - 60 Hz, 460 W	120 V - 60 Hz, 460 W	120 V - 60 Hz, 460 W
Kits Available	CFC0141725AUL (Recirculating Kit)	CFC0141725AUL (Recirculating Kit)	CFC0141725AUL (Recirculating Kit)	CFC0141725AUL (Recirculating Kit)

SPECS

Ceiling Hoods

				
Model Name	Illusion Iconic Series	Hilight Iconic Series		
Model Numbers	EIL640DW EIL640WH	EHL640SS EHL640WH		
Dimensions	40" W x 19 17/25" D	40" W x 22 11/25" D		
Blower Type	600 CFM (3 speed + boost)	600 CFM (3 speed + boost)		
CFM Reduction	No	No		
Noise (sones)	6.8 Sones	6.8 Sones		
Finish	Panel ready naked panel (stainless steel) + Stainless Steel Frame Metal White with White Frame	Stainless Steel White Glass with Metal White Frame		
Controls	Remote control	Remote control		
Illumination	2 Strip LED 14 W with dimmable and tunable lightning	2 Strip LED 14 W with dimmable and tunable lightning		
Filter Type	Aluminum Mesh Filter + Perimeter Aspiration	Aluminum Mesh Filter + Perimeter Aspiration		
Duct Transition	6" Round Multidirectional	6" Round Multidirectional		
Installation Type	Ducted or recirculating with kit	Ducted or recirculating with kit		
Electrical	120 V - 60 Hz, 578 W	120 V - 60 Hz, 578 W		
Kits Available	KIT0167875 (Recirculating Kit)	KIT0167875 (Recirculating Kit)		

SPECS

Wall Mount Hoods

		
Model Name	Oristano	Catania
Model Numbers	EORX36SS (requires EAR634SS or EAR134S4) EORX48SS (requires EAR140S4)	ECTX36SS (requires ETR634SS or ETR134S1) ECTX48SS (requires ETR146SS)
Dimensions	36" W x 24" D x 30"H 48" W x 24" D x 30"H	36" W x 22" D x 34"H 48" W x 22" D x 34"H
Blower Type (Sold separately)	600 CFM (4-speed) - 1200 CFM (4-speed)* **requires Arezzo insert	600 CFM (4-speed) - 1200 CFM (4-speed)* **requires Trento insert
CFM Reduction	No	No
Noise (sones)	7 Sones 8.5 Sones*	7 Sones 8.5 Sones*
Finish	Stainless Steel + Front and lateral Rim - Stainless steel Mirror look + Decorative bands & bolts - Stainless steel Mirror look (2 for 36" & 3 for 48")	Stainless Steel + Front Rim - Stainless steel Mirror look + Decorative bands & bolts - Stainless steel Mirror look (4 for 36" & 5 for 48")
Controls	Fully Retractable Rotating Knobs w/ Blue Backlighting	Fully Retractable Rotating Knobs w/ Blue Backlighting
Illumination	2 LED, 6.5 w, 3000K, 540 lumen 4 LED, 6.5 w, 3000K 540 lumen	2 LED, 6.5 w, 3000 K,540 lumen
Installation	Elica Easy Mounting + Rear Outlet installation	Elica Easy Mounting + Rear Outlet installation
Filter Type	Dishwasher-Safe, Professional Stainless Steel Angled Baffle Filter	Dishwasher-Safe, Professional Stainless Steel Angled Baffle Filter
Duct Transition	10" Round with Back Draft Damper (Top only)	10" Round with Back Draft Damper (Top only)
Kits Available	36" width: KIT0182781 (Duct cover extension 6") KIT0182782 (Duct cover extension 18") 48" width: KIT0182783 (Duct cover extension 6") KIT0182784 (Duct cover extension 18")	36" width: KIT0182785 (Duct cover extension 6") KIT0182786 (Duct cover extension 18") 48" width: KIT0182787 (Duct cover extension 6") KIT0182788 (Duct cover extension 18")


SPECS

Special Configurations

				
Model Name	Rise Techne Series	Capri Elica Pro Series		
Model Numbers	ERS630S1 ERS636S1	ECP136SS ECP148SS		
Dimensions	30"W x 12 1/2"D x 14"H 36"W x 12 1/2"D x 14"H	36"W x 32"D x 18"H 48"W x 32"D x 18"H		
Blower Type	600 CFM (3-speed + boost)	1200 CFM(4-speed) Internal or external		
CFM Reduction	Yes, with Kit	No		
Noise (sones)	6.8 Sones	8.5 Sones		
Finish	Stainless Steel	Corrosion Resistant Grade Stainless Steel		
Controls	External Electronic Rotating Disk + LCD	Fully Retractable Rotating Knobs w/ Blue Backlighting		
Illumination	No Lightning	2 LED, 7.5 W (36") 4 LED, 7.5 W(48") *Consumer Replaceable		
Filter Type	Aluminum Mesh Filter + Perimeter Aspiration	Dishwasher-Safe, Professional Stainless Steel (4w/36", 6w/48")		
Duct Transition	6" Round with Back Draft Damper (Side)	10" Round with Back Draft Damper (Top Only)		
Installation Type	Ducted Installation Only	Ducted Installation Only		
Electrical	120 V - 60 Hz, 550 W	120 V - 60 Hz 913 W		
Kits Available	KIT02748 (CFM reduction)	KIT0153054 (External blower) KIT0154387 (In-line blower) KIT0156655 (Internal blower)		

SPECS

Aspiration & Induction Cooktops

		
Model Name	NikolaTesla Switch	
Model Numbers	ENS436BL	
Dimensions	36" W x 20 1/4"D x 8 1/4"H	
Blower Type	400 CFM (3-speed + boost)	
Noise (sones)	5.9 Sones	
Cooking Zones:	4 zones of 7.1" x 7.9"	
Heating Level:	9 Levels + Booster	
Finish	Deep - Black Glass	
Controls	Slider touch control 3 speed + Booster ventilation	
Installation Type:	Ducted or recirculating Self rimming or flush mounted	
Filter Specification:	6 Layer Anodized Aluminum Mesh Grease Filter	
Electrical	208 - 240 V - 60 Hz 440 Watts at 3.3 Amps 240 V - 7.8 kW at 32.5 Amps 208 V - 7.1 kW at 34.1 Amps	
Kits Available		

SPECS

RISERVA Series - Undercounter Refrigeration

				
Model Name	Beverage & Wine Center FRENCH DOOR DUAL ZONE	Beverage Center SINGLE DOOR SINGLE ZONE	Beverage & Wine Center SINGLE DOOR DUAL ZONE	Wine Cellar SINGLE DOOR DUAL ZONE
Model Numbers	EBF52SS1	EBS51SS1	EBS52SS1	EWS52SS1
Dimensions	23 13/32" W x 34 13/16" H x 22 13/32" D	23 13/32" W x 33 13/16" H x 23 5/8" D	23 13/32" W x 33 13/16" H x 23 5/8"	23 13/32" W x 33 13/16" H x 23 5/8" D
Volume (Capacity)	4.8 cu ft (135L) Cooling Zone 1: > 60 Cans (12 oz) Cooling Zone 2: 21 Bottles of Wine (25 oz)	4.8 cu ft (135L) > 120 Cans (12 oz)	4.8 cu ft (135L) Cooling Zone 1: 72 Cans (12 oz) Cooling Zone 2: 14 Bottles of Wine (25 oz)	4.8 cu ft (135L) Cooling Zone 1: 16 Bottles of Wine (25 oz) Cooling Zone 2: 36 Bottles of Wine (25 oz)
Temperature Range	34 to 68 °F	34 to 65°F	34 to 50°F 40 to 64° F	40 to 50°F 50 to 64° F
Refrigerant Type	R600a	R600a	R600a	R600a
Finish	Door: 304 Stainless Steel + UV Tempered Glass Cabinet/ Interior: Black Shelving: 3 tempered Glass + 6 Beechwood with metal front rim	Door: 304 Stainless Steel + UV Tempered Glass Cabinet/ Interior: Black Shelving: 3 Slide Out Tempered Glass Shelves with metal front trim.	Door: 304 Stainless Steel + UV Tempered Glass Cabinet/ Interior: Black Shelving: 2 Slide Out Tempered Glass + 1 Beechwood with metal front rim	Door: 304 Stainless Steel + UV Tempered Glass Cabinet/ Interior: Black Shelving: 5 Beechwood with metal front rim
Illumination	3 Level White LED	3 Level White LED	3 Level White LED	3 Level White LED
Controls	Capacitive Touch Display with white numbers	Capacitive Touch Display with white numbers	Capacitive Touch Display with white numbers	Capacitive Touch Display with white numbers
Noise	39 dBA	39 dBA	39 dBA	39 dBA
Electrical	110-120 V / 60 Hz / 0.95 A Min. Circuit: 15 A	110-120 V / 60 Hz / 0.95 A Min. Circuit: 15 A	110-120 V / 60 Hz / 0.95 A Min. Circuit: 15 A	110-120 V / 60 Hz / 0.95 A Min. Circuit: 15 A
Features	Perfect Climate Technology Full extension Racks Anti Vibration Technology Eco Mode Quiet Operation Sabbath Mode	Perfect Climate Technology Full extension Racks Anti Vibration Technology Eco Mode Quiet Operation Sabbath Mode	Perfect Climate Technology Full extension Racks Anti Vibration Technology Eco Mode Quiet Operation Sabbath Mode	Perfect Climate Technology Full extension Racks Anti Vibration Technology Eco Mode Quiet Operation Sabbath Mode
Kits Available	KIT0175505 (Pro Handle) L00114-1 (Carbon Filter)	KIT0175505 (Pro Handle) L00114-1 (Carbon Filter)	KIT0175505 (Pro Handle) L00114-1 (Carbon Filter)	KIT0175505 (Pro Handle) L00114-1 (Carbon Filter)

