

FISHER & PAYKEL

36" PROFESSIONAL RANGES & BACKGUARDS

RDV3-366

BGRV2-1236, BGRV2-3036, BGRV3-3036H models

PLANNING GUIDE



OVERVIEW

Elevate any kitchen design with the Dual Fuel Range, 36". This range offers an intuitive, high-resolution touch display, six-burner gas rangetop, an electronic oven with generous capacity and comprehensive cooking functions to deliver perfect results. Power and style combined beautifully.

PRODUCTS

RDV3-366-N
Dual Fuel Range, 36", 6 Burners

RDV3-366-L
Dual Fuel Range, 36", 6 Burners, LPG

SERIES & STYLE

Series 9
Professional

FEATURES

- 1 Stainless steel
- 2 High-resolution, user-friendly touch display
- 3 Metal illuminated dials
- 4 Electronic oven control
- 5 Perfect results from 15 oven functions
- 6 Guided cooking by food type and recipes
- 7 4.8 cu ft-capacity oven
- 8 Self-cleaning oven with pyrolytic ladders
- 9 Sealed Dual Flow Burners™
- "0 Dishwasher-proof, cast-iron trivets


ACCESSORIES

- 1 Food probe
- 2 Broil pan
- 3 Broil rack
- 4 Full-extension telescopic racks

The models shown in this Planning Guide may not be available in all markets and are subject to change at any time. Product specifications may vary from those shown. This Planning Guide should not be used as installation guidance for any product. Further information is required to safely and correctly install the products featured here. Specific installation guidance will be available on our website fisherpaykel.com


SPECIFICATIONS	
Model No.	RDV3-366-N, RDV3-366-L
Product Dimensions	H 35 3/4" – 36 3/4" (908-933mm) W 35 7/8" (911mm) D 29 1/8" (740mm)
Weight	440lb (200kg)
Total oven capacity	4.8 cu ft (136L)
Door Clearance	19 1/8" (486mm)
Gas	
Types	Natural Gas 6" to 9" W.C.P. LP Propane 11" to 14" W.C.
Connection	1/2" NPT Minimum 5/8" dia. flex line
Electrical	
Supply	120/240 V, 60 Hz
Service	30 A
Connection	4-prong grounding type (NEMA 14-50 plug)

PRODUCT DIMENSIONS



	mm	Inch
A Overall height (from floor to cooktop, excl. grates and vent trim)	min 908 max 933	min 35 3/4 max 36 3/4
B Overall width	911	35 7/8
C Depth from front of range to rear (incl. vent trim, excl. dials and handle)	740	29 1/8

CAVITY DIMENSIONS: STANDARD INSTALLATION



	mm	Inch
A Overall height of cavity* • for level counter • with range levelling legs fully extended	908 933	35 3/4 36 3/4
B Overall width of cavity	914	36
C Maximum depth of cavity • projecting control panel • flush control panel	644 703	25 3/8 27 11/16

*Depending on height of range

The models shown in this Planning Guide may not be available in all markets and are subject to change at any time. Product specifications may vary from those shown. This Planning Guide should not be used as installation guidance for any product. Further information is required to safely and correctly install the products featured here. Specific installation guidance will be available on our website fisherpaykel.com

CONTENTS

36" Professional Range	PAGE	
RDV3-366	in	mm
Key Design Decisions	6	15
Ventilation Requirements	7	16
36" Professional Range		
RDV3-366-N, RDV3-366-L		
Product & Cavity Dimensions	8	17
Clearance Dimensions	9	18
Cavity Preparation	10	19
36" Professional Range Backguard		
BGRV2-1236	in	mm
Product Dimensions	11	20
36" Professional Range Backguard		
BGRV2-3036		
Product Dimensions	12	21
36" Professional Range Backguard		
BGRV3-3036H		
Product Dimensions	13	22


IMPERIAL

FISHER & PAYKEL

KEY DESIGN DECISIONS 36" Professional Range

1


INSTALL TYPE




WALL

2

REAR SURFACE



COMBUSTIBLE




NON COMBUSTIBLE


ISLAND

3


BACKGUARD OPTIONS




NO BACKGUARD




LOW THIN BACKGUARD




HIGH THICK BACKGUARD
WITH ANGLED TRIM



NO BACKGUARD



CUSTOM FABRICATED* BACKGUARD
*Fabricated from non combustibile materials only



HIGH THIN BACKGUARD

Model no:
RDV3-366

DATE: **20.06.2024**


ghout this guide, dimensions may vary by $\pm 2\text{mm}$ (1/16").
Read the installation guide for detailed information on installing the product.
For full installation instructions and specifications visit fisherpaykel.com

FISHER & PAYKEL


VENTILATION REQUIREMENTS 36" Professional Range

1

INSTALL TYPE




WALL




ISLAND

2


HOOD SURROUND MATERIAL




NON COMBUSTIBLE



COMBUSTIBLE



NON COMBUSTIBLE



COMBUSTIBLE

Model no:
RDV3-366

Specifications

Ventilation Unit

Hood

Blower

Wall Installation

Minimum 19" Deep x Unit Width

Minimum 550 CFM

Ventilation Unit

Hood

Blower

Island Installation

Minimum 19" Deep x Unit Width

Minimum 550 CFM

Note: A suitable hood must be installed above the range. The above indicates the minimum blower capacity recommended for hood ventilation.

*Recommended maximum.

DATE: **20.06.2024**

Throughout this guide, dimensions may vary by $\pm 2\text{mm}$ (1/16").
Read the installation guide for detailed information on installing the product.
For full installation instructions and specifications visit fisherpaykel.com

FISHER & PAYKEL

PRODUCT & CAVITY DIMENSIONS 36" Professional Range - Dual Fuel

Model no:

RDV3-366

Product Dimensions	in
a Height of range (from floor to cooktop, excluding grates and rear trim)	min 35 3/4" max 36 3/4"
B Overall width of range	35 7/8"
c Overall depth of range (excluding handle and dials)	29 1/8"
d Depth from rear of chassis to cabinetry face - projecting	25 3/8"
e Depth from rear of chassis to cabinetry face - flush	27 11/16"
f Height from countertop to top of pan supports	19 1/16"
g Height of rear trim	1 3/4"
H Depth of rear trim	2 7/8"
i Height from countertop to bottom of control panel	7 3/4"
j Height from countertop to top of door	8 1/8"
k Height from countertop to centre of handle	9 7/16"
l Height from countertop to bottom of door	29"
m Height from countertop to top of lower panel	29 15/16"
n Height from countertop to bottom of lower panel	33 5/8"
o Thickness of handle (not including standoffs)	1 1/4"
p Width of handle (including standoffs)	35 1/8"
q Depth of handle (measured from front of door)	2 7/8"
r Depth of front of cooktop to control panel	17 1/16"
s Height of cooktop front face	1 3/8"
t Height from top of cooktop to control panel	2"
u Depth of open door to cabinetry face - flush	19 1/8"
v Adjustable feet height	min 1/2" max 1 1/2"


Cavity Dimensions	mm
Overall width of cavity	min 36"
Overall depth of cavity for projecting control panel	max 25 3/8"
Overall depth of cavity for flush control panel	max 27 11/16"
Overall height of cavity	35 3/4" 36 3/4"

IMPORTANT NOTE: For full installation and clearance details please refer to our installation manual.

INDICATES CAVITY CLEARANCES -----
INDICATES PRODUCT DATUM - - - - -

DATE: **20.06.2024**

ghout this guide, dimensions may vary by ±2mm (1/16").
Read the installation guide for detailed information on installing the product.
For full installation instructions and specifications visit fisherpaykel.com



FISHER & PAYKEL


CLEARANCE DIMENSIONS 36" Professional Range - Dual Fuel

Model no:
RDV3-366

Clearance Dimensions	in
a Minimum width of ventilation hood installed above range - not shown*	36"
B Minimum vertical distance between countertop and cabinet extending above counter	18"
c Minimum clearance from left and right of range to nearest vertical combustible surface	12"
d Minimum clearance from cooking surface to: - combustible surface centered above the cooking surface - combustible covering for ventilation hood centered above the cooking surface - non-combustible surface** centered above the cooking surface	54" 36" 30"
e Maximum overall depth of overhead cabinetry	13"
f Distance from center of rear burner to rear of product	8 5/8"

*IMPORTANT NOTE: For full installation and clearance details please refer to our installation manual.

**Non-combustible surfaces: as defined in 'National Fuel Gas Code' (ANSI Z223.1, Current Edition). Clearances from non-combustible materials are not part of the ANSI Z21.1 scope and are not certified by UL. Clearances of less than 6" (152mm) must be approved by the local codes and/or by the local authority having jurisdiction.



INDICATES CLEARANCES - - - - -
INDICATES PRODUCT DATUM - - - - -

DATE: **20.06.2024**

IMPORTANT: Throughout this guide, dimensions may vary by ±2mm (1/16"). Read the installation guide for detailed information on installing the product. For full installation instructions and specifications visit fisherpaykel.com



FISHER & PAYKEL


CAVITY PREPARATION 36" Professional Range - Dual Fuel

Model no:
RDV3-366

Specifications	
Oven Total Capacity	4,8 cu.ft
Electrical	
Supply	120/240 V, 60 Hz
Service	30 A
Connection	4-prong grounding type (NEMA 14-50P plug)
Gas	
Types	Natural Gas 6" to 9" W.C. LP Propane 11" to 14" W.C.
Connection	1/2" NPT Minimum 5/8" dia. flex line

*Regulator location may vary depending on model.

IMPORTANT NOTE: For full installation and connection details please refer to our installation manual.





DATE: **20.06.2024**

IMPORTANT: Throughout this guide, dimensions may vary by ±2mm (1/16"). Read the installation guide for detailed information on installing the product. For full installation instructions and specifications visit fisherpaykel.com


FISHER & PAYKEL

PRODUCT DIMENSIONS


36" Professional Range Backguard




PLAN VIEW



PROFILE VIEW



FRONT VIEW



Model no:
BGRV2-1236

Product Dimensions	in
A Height of backguard above vent trim on range	10 3/8"
B Overall height of backguard	15 15/16"
C Overall width of backguard	35 7/8"
D Overall depth of backguard	1/2"
E Height of backguard below vent trim on range	5 9/16"
F Depth of backguard below vent trim on range	1/16"

INDICATES PRODUCT DATUM -----

DATE: **20.06.2024**




IMPORTANT: Throughout this guide, dimensions may vary by $\pm 2\text{mm}$ (1/16"). Read the installation guide for detailed information on installing the product. For full installation instructions and specifications visit fisherpaykel.com

FISHER & PAYKEL

PRODUCT DIMENSIONS 36" Professional Range Backguard

Model no:
BGRV2-3036


Product Dimensions	in
A Height of backguard above vent trim on range	28 3/8"
B Overall height of backguard	29 1/8"
C Overall width of backguard	35 7/8"
D Overall depth of backguard and racks	9 5/16"
E Depth of backguard	1/2"
F Depth of racks	8 13/16"
G Width of racks	34"
H Distance from top of backguard to bottom of racks	10 15/16"
I Distance from bottom of backguard to bottom of racks	17 3/8"
J Distance from top of backguard to top of brackets	5 7/8"
K Height of backguard below vent trim on range	13/16"
L Depth of backguard below vent trim on range	1/16"



INDICATES PRODUCT DATUM -----

DATE: **20.06.2024**

IMPORTANT: Throughout this guide, dimensions may vary by $\pm 2\text{mm}$ (1/16"). Read the installation guide for detailed information on installing the product. For full installation instructions and specifications visit [fisherpaykel.com](https://www.fisherpaykel.com)



FISHER & PAYKEL





PRODUCT DIMENSIONS

36" Professional Range Backguard with Angled Vent Trim

Model no:
BGRV3-3036H

Product Dimensions	in
A Overall height of backguard with angled vent trim	30"
B Overall width of backguard	35 7/8"
C Overall depth of backguard and racks	10 3/8"
D Height of backguard	26 1/2"
E Height of angled vent trim	3 1/2"
F Depth of angled vent trim	2 7/8"
G Depth of backguard	1 5/16"
H Depth of racks	9 1/16"
I Width of racks	33 15/16"
J Distance from top of backguard to top of racks	5 3/8"
K Distance from bottom of angled vent trim to bottom of racks	18 7/8"


Note: Angled vent trim supplied with BGRV3-3036H.
Remove flat vent trim and replace with angled vent trim.



INDICATES PRODUCT DATUM -----

DATE: **20.06.2024**

IMPORTANT: Throughout this guide, dimensions may vary by ±2mm (1/16").
Read the installation guide for detailed information on installing the product.
For full installation instructions and specifications visit fisherpaykel.com




METRIC

FISHER & PAYKEL

KEY DESIGN DECISIONS 36" Professional Range

1


INSTALL TYPE




WALL

2


REAR SURFACE



COMBUSTIBLE




NON COMBUSTIBLE




ISLAND

3


BACKGUARD OPTIONS




NO BACKGUARD



NO BACKGUARD




LOW THIN BACKGUARD




CUSTOM FABRICATED* BACKGUARD

*Fabricated from non combustible materials only



HIGH THICK BACKGUARD
WITH ANGLED TRIM



HIGH THIN BACKGUARD

Model no:
RDV3-366

DATE: **20.06.2024**


IMPORTANT: Throughout this guide, dimensions may vary by $\pm 2\text{mm}$ (1/16").
Read the installation guide for detailed information on installing the product.
For full installation instructions and specifications visit fisherpaykel.com

FISHER & PAYKEL


VENTILATION REQUIREMENTS 36" Professional Range

1

INSTALL TYPE




WALL




ISLAND

2


HOOD SURROUND MATERIAL




NON COMBUSTIBLE



COMBUSTIBLE



NON COMBUSTIBLE



COMBUSTIBLE

Model no:
RDV3-366

Specifications

Ventilation Unit

Hood
Blower

Wall Installation

Minimum 480mm Deep x Unit Width
Minimum 550 CFM

Ventilation Unit

Hood
Blower

Island Installation

Minimum 480mm Deep x Unit Width
Minimum 550 CFM

Note: A suitable hood must be installed above the range. The above indicates the minimum blower capacity recommended for hood ventilation.

*Recommended maximum.

DATE: **20.06.2024**

IMPORTANT: Throughout this guide, dimensions may vary by $\pm 2\text{mm}$ (1/16"). Read the installation guide for detailed information on installing the product. For full installation instructions and specifications visit fisherpaykel.com

FISHER & PAYKEL

PRODUCT & CAVITY DIMENSIONS 36" Professional Range - Dual Fuel

Model no:
RDV3-366

Product Dimensions	mm
a Height of range (from floor to cooktop, excluding grates and rear trim)	min 908 max 933
B Overall width of range	911
c Overall depth of range (excluding handle and dials)	740
d Depth from rear of chassis to cabinetry face - projecting	644
e Depth from rear of chassis to cabinetry face - flush	703
f Height from countertop to top of pan supports	40
g Height of rear trim	45
H Depth of rear trim	73
i Height from countertop to bottom of control panel	196
j Height from countertop to top of door	206
k Height from countertop to centre of handle	239
l Height from countertop to bottom of door	737
m Height from countertop to top of lower panel	761
n Height from countertop to bottom of lower panel	855
o Thickness of handle (not including standoffs)	32
p Width of handle (including standoffs)	892
q Depth of handle (measured from front of door)	73
r Depth of front of cooktop to control panel	37
s Height of cooktop front face	35
t Height from top of cooktop to control panel	51
u Depth of open door to cabinetry face - flush	486
v Adjustable feet height	min 13 max 38


Cavity Dimensions	mm
Overall width of cavity	min 914
Overall depth of cavity for projecting control panel	max 644
Overall depth of cavity for flush control panel	max 703
Overall height of cavity	908 933

IMPORTANT NOTE: For full installation and clearance details please refer to our installation manual.

INDICATES CAVITY CLEARANCES -----
INDICATES PRODUCT DATUM - - - - -

DATE: **20.06.2024**

IMPORTANT: Throughout this guide, dimensions may vary by ±2mm (1/16"). Read the installation guide for detailed information on installing the product. For full installation instructions and specifications visit fisherpaykel.com



FISHER & PAYKEL


CLEARANCE DIMENSIONS 36" Professional Range - Dual Fuel

Model no:
RDV3-366

Clearance Dimensions	mm
a Minimum width of ventilation hood installed above range - not shown*	914
B Minimum vertical distance between countertop and cabinet extending above counter	457
c Minimum clearance from left and right of range to nearest vertical combustible surface	305
d Minimum clearance from cooking surface to: - combustible surface centred above the cooking surface - combustible covering for ventilation hood centred above the cooking surface - non-combustible surface** centred above the cooking surface	1372 914 762
e Maximum overall depth of overhead cabinetry	330
f Distance from centre of rear burner to rear of product	218

*IMPORTANT NOTE: For full installation and clearance details please refer to our installation manual.

**Non-combustible surfaces: as defined in 'National Fuel Gas Code' (ANSI Z223.1, Current Edition). Clearances from non-combustible materials are not part of the ANSI Z21.1 scope and are not certified by UL. Clearances of less than 6" (152mm) must be approved by the local codes and/or by the local authority having jurisdiction.



INDICATES CLEARANCES - - - - -
INDICATES PRODUCT DATUM - - - - -

DATE: **20.06.2024**

IMPORTANT: Throughout this guide, dimensions may vary by $\pm 2\text{mm}$ ($1/16"$). Read the installation guide for detailed information on installing the product. For full installation instructions and specifications visit fisherpaykel.com

FISHER & PAYKEL


CAVITY PREPARATION 36" Professional Range - Dual Fuel

Model no:
RDV3-366

Specifications	
Oven Total Capacity	136L
Electrical	
Supply	120/240 V, 60 Hz
Service	30 A
Connection	4-prong grounding type (NEMA 14-50P plug)
Gas	
Types	Natural Gas 6" to 9" W.C. LP Propane 11" to 14" W.C.
Connection	1/2" NPT Minimum 5/8" dia. flex line

*Regulator location may vary depending on model.

IMPORTANT NOTE: For full installation and connection details please refer to our installation manual.



DATE: **20.06.2024**

IMPORTANT: Throughout this guide, dimensions may vary by ±2mm (1/16"). Read the installation guide for detailed information on installing the product. For full installation instructions and specifications visit fisherpaykel.com



FISHER & PAYKEL

PRODUCT DIMENSIONS


36" Professional Range Backguard

Model no:
BGRV2-1236


Product Dimensions	mm
A Height of backguard above vent trim on range	263
B Overall height of backguard	405
C Overall width of backguard	911
D Overall depth of backguard	13
E Height of backguard below vent trim on range	142
F Depth of backguard below vent trim on range	1



PLAN VIEW



PROFILE VIEW



FRONT VIEW



INDICATES PRODUCT DATUM -----

DATE: **20.06.2024**



IMPORTANT: Throughout this guide, dimensions may vary by $\pm 2\text{mm}$ (1/16"). Read the installation guide for detailed information on installing the product. For full installation instructions and specifications visit fisherpaykel.com

FISHER & PAYKEL


PRODUCT DIMENSIONS 36" Professional Range Backguard

Model no:
BGRV2-3036

Product Dimensions	mm
A Height of backguard above vent trim on range	720
B Overall height of backguard	740
C Overall width of backguard	911
D Overall depth of backguard and racks	237
E Depth of backguard	13
F Depth of racks	224
G Width of racks	864
H Distance from top of backguard to bottom of racks	278
I Distance from bottom of backguard to bottom of racks	442
J Distance from top of backguard to top of brackets	149
K Height of backguard below vent trim on range	20
L Depth of backguard below vent trim on range	1



PLAN VIEW



FRONT VIEW



INDICATES PRODUCT DATUM -----

DATE: **20.06.2024**

IMPORTANT: Throughout this guide, dimensions may vary by $\pm 2\text{mm}$ (1/16").
Read the installation guide for detailed information on installing the product.
For full installation instructions and specifications visit fisherpaykel.com

FISHER & PAYKEL





PRODUCT DIMENSIONS

36" Professional Range Backguard with Angled Vent Trim

Model no:
BGRV3-3036H

Product Dimensions	mm
A Overall height of backguard with angled vent trim	763
B Overall width of backguard	911
C Overall depth of backguard and racks	264
D Height of backguard	673
E Height of angled vent trim	90
F Depth of angled vent trim	72
G Depth of backguard	33
H Depth of racks	230
I Width of racks	862
J Distance from top of backguard to top of racks	136
K Distance from bottom of angled vent trim to bottom of racks	480

Note: Angled vent trim supplied with BGRV3-3036H.
Remove flat vent trim and replace with angled vent trim.



INDICATES PRODUCT DATUM -----

DATE: **20.06.2024**

IMPORTANT: Throughout this guide, dimensions may vary by $\pm 2\text{mm}$ (1/16").
Read the installation guide for detailed information on installing the product.
For full installation instructions and specifications visit fisherpaykel.com

IMPORTANT: The product dimensions and specifications apply at the date of issue. Under our policy of continuous product improvement, these dimensions and specifications may change at any time. Dimensions may vary by $\pm 2\text{mm}$ (1/16"). Please read the installation guide for detailed information on installing the product or visit fisherpaykel.com.

June 2024